AIR QUALITY and GHG IMPACT ANALYSES

13811 VALLEY VIEW AVENUE APN 8059-028-049

LA MIRADA, CALIFORNIA

Prepared by:

Giroux & Associates 1800 E Garry St., #205 Santa Ana, CA 92705

Prepared for:

Phil Martin & Associates Attn: Phil Martin 4860 Irvine Boulevard, Suite 203 Irvine, CA 92620

Date:

June 18, 2019

Project No.: P19-023 A

ATMOSPHERIC SETTING

The project site's climate, as with all Southern California, is dominated by the strength and position of the semi-permanent high pressure pattern over the Pacific Ocean near Hawaii. It creates cool summers, mild winters, and infrequent rainfall. It drives the cool daytime sea breeze, and it maintains comfortable humidity levels and ample sunshine after the frequent morning clouds dissipate. Unfortunately, the same atmospheric processes that create the desirable living climate combine to restrict the ability of the atmosphere to disperse the air pollution generated by the large population attracted in part by the desirable climate. Portions of the Los Angeles Basin therefore experience some of the worst air quality in the nation for certain pollutants.

Temperatures in the La Mirada vicinity average 63 degrees annually. Daily and seasonal oscillations of temperature are small because of the moderating effects of the nearby oceanic thermal reservoir. Summer afternoons reach 90 degrees on average, and winter mornings drop to 40 degrees. In contrast to the steady temperature regime, rainfall is highly variable. Measurable precipitation occurs mainly from early November to mid-April, but total amounts are generally small. The La Mirada area averages 15 inches of rain annually with January as the wettest month. Twenty-two days per year have measurable rain, with moderate to heavy rain (>0.50 inch in 24 hours) on seven days.

Winds in the project vicinity display several characteristic regimes. During the day, especially in summer, winds are from the southwest in the morning and from the northwest in the afternoon. Daytime wind speeds are 6-8 miles per hour on average. At night, especially in winter, the land becomes cooler than the ocean, and an offshore wind of 2-4 miles per hour develops. One other important wind regime occurs when high pressure occurs over the western United States that creates hot, dry and gusty Santa Ana winds from the north and northeast across La Mirada.

The net effect of the wind pattern on air pollution is that any locally generated emissions will be carried seaward at night and toward western Riverside or San Bernardino Counties by day. Daytime ventilation is much more vigorous. Unless daytime winds rotate far into the northwest and bring air pollution from developed areas of the air basin into La Mirada, warm season air quality is better in the project vicinity than in inland valleys farther to the east. While winter mornings have strong stagnation potential because of light winds, automobiles have become sufficiently "clean" such that localized pollution "hot spots" have almost completely disappeared. Although there are still recurring violations of some clean air standards, the magnitude and frequency of those violations have diminished dramatically in the last 20-30 years in the project area.

In addition to winds that control the rate and direction of pollution dispersal, Southern California is notorious for strong temperature inversions that limit the vertical depth through which pollution can be mixed. In summer, coastal areas are characterized by a sharp discontinuity between the cool marine air at the surface and the warm, sinking air aloft within the high-pressure cell over the ocean to the west. This marine/subsidence inversion allows for good local mixing but acts like a giant lid over the basin. Air starting onshore at the beach is relatively clean but becomes progressively more polluted as sources continue to add pollution from below without any dilution

from above. La Mirada is only moderately affected by the marine inversion such that the frequency of violations of smog standards is relatively low.

A second inversion type forms on clear, winter nights when cold air off the mountains sinks to the surface while the air aloft remains warm. This process forms radiation inversions. These inversions, in conjunction with calm winds, trap pollutants such as automobile exhaust near their source. During the long nocturnal drainage flow from land to sea, the exhaust pollutants continually accumulate within the shallow, cool layer of air near the ground. Some areas of Orange County thus may experience slightly elevated levels of carbon monoxide and nitrogen oxides because of this winter radiation inversion condition. However, the La Mirada area is not substantially affected by limited nocturnal mixing effects (no violations of CO standards in almost 20 years). Both types of inversions occur throughout the year to some extent, but the marine inversions are very dominant during the day in summer, and radiation inversions are much stronger on winter nights when nights are long, and air is cool. The governing role of these inversions in atmospheric dispersion leads to a substantially different air quality environment in summer in the South Coast Air Basin than in winter.

AIR QUALITY SETTING

AMBIENT AIR QUALITY STANDARDS (AAQS)

In order to gauge the significance of the air quality impacts of the proposed project, those impacts, together with existing background air quality levels, must be compared to the applicable ambient air quality standards. These standards are the levels of air quality considered safe, with an adequate margin of safety, to protect the public health and welfare. They are designed to protect those people most susceptible to further respiratory distress such as asthmatics, the elderly, very young children, people already weakened by other disease or illness, and persons engaged in strenuous work or exercise, called "sensitive receptors." Healthy adults can tolerate occasional exposure to air pollutant concentrations considerably above these minimum standards before adverse effects are observed. Recent research has shown, however, that chronic exposure to ozone (the primary ingredient in photochemical smog) may lead to adverse respiratory health even at concentrations close to the ambient standard.

National AAQS were established in 1971 for six pollution species with states retaining the option to add other pollutants, require more stringent compliance, or to include different exposure periods. The initial attainment deadline of 1977 was extended several times in air quality problem areas like Southern California. In 2003, the Environmental Protection Agency (EPA) adopted a rule, which extended and established a new attainment deadline for ozone for the year 2021. Because the State of California had established AAQS several years before the federal action and because of unique air quality problems introduced by the restrictive dispersion meteorology, there is considerable difference between state and national clean air standards. Those standards currently in effect in California are shown in Table 1. Sources and health effects of various pollutants are shown in Table 2.

The Federal Clean Air Act Amendments (CAAA) of 1990 required that the U.S. Environmental Protection Agency (EPA) review all national AAQS in light of currently known health effects. EPA was charged with modifying existing standards or promulgating new ones where appropriate. EPA subsequently developed standards for chronic ozone exposure (8+ hours per day) and for very small diameter particulate matter (called "PM-2.5"). New national AAQS were adopted in 1997 for these pollutants.

Planning and enforcement of the federal standards for PM-2.5 and for ozone (8-hour) were challenged by trucking and manufacturing organizations. In a unanimous decision, the U.S. Supreme Court ruled that EPA did not require specific congressional authorization to adopt national clean air standards. The Court also ruled that health-based standards did not require preparation of a cost-benefit analysis. The Court did find, however, that there was some inconsistency between existing and "new" standards in their required attainment schedules. Such attainment-planning schedule inconsistencies centered mainly on the 8-hour ozone standard. EPA subsequently agreed to downgrade the attainment designation for a large number of communities to "non-attainment" for the 8-hour ozone standard.

Table 1

		Ambient A	Air Qualit	y Standaro	ds		
Pollutant	Averaging	California Standards ¹		National Standards ²			
Poliulani	Time	Concentration ³	Method ⁴	Primary ^{3,5}	Secondary ^{3,6}	Method ⁷	
Ozone (O₂) ⁸	1 Hour	0.09 ppm (180 µg/m ³)	Ultraviolet	-	Same as	Ultraviolet	
	8 Hour	0.070 ppm (137 µg/m ³)	Photometry	0.070 ppm (137 µg/m ³)	Primary Standard	Photometry	
Respirable Particulate	24 Hour	50 µg/m³	Gravimetric or	150 µg/m³	Same as	Inertial Separation	
Matter (PM10) ⁹	Annual Arithmetic Mean	20 µg/m³	Beta Attenuation	—	Primary Standard	Analysis	
Fine Particulate	24 Hour	_	_	35 μg/m ³	Same as Primary Standard	Inertial Separation	
Matter (PM2.5) ⁹	Annual Arithmetic Mean	12 µg/m ³	Gravimetric or Beta Attenuation	12.0 µg/m³	15 µg/m³	Analysis	
Carbon	1 Hour	20 ppm (23 mg/m ³)	Nen Dienerrier	35 ppm (40 mg/m ³)	_	Non-Dispersive Infrared Photometry (NDIR)	
Monoxide	8 Hour	9.0 ppm (10 mg/m ³)	Infrared Photometry (NDIR)	9 ppm (10 mg/m ³)	_		
(00)	8 Hour (Lake Tahoe)	6 ppm (7 mg/m ³)	(_	-		
Nitrogen Dioxide	1 Hour	0.18 ppm (339 µg/m ³)	Gas Phase	100 ppb (188 µg/m³)	_	Gas Phase	
(NO ₂) ¹⁰	Annual Arithmetic Mean	0.030 ppm (57 µg/m ³)	Chemiluminescence	0.053 ppm (100 µg/m ³)	Same as Primary Standard	Chemiluminescence	
	1 Hour	0.25 ppm (655 µg/m ³)		75 ppb (196 µg/m ³)	_		
Sulfur Dioxide	3 Hour	_	Ultraviolet	_	0.5 ppm (1300 μg/m ³)	Ultraviolet Flourescence; Spectrophotometry (Pararosaniline Method)	
(SO ₂)''	24 Hour	0.04 ppm (105 µg/m ³)	Fluorescence	0.14 ppm (for certain areas) ¹¹	_		
	Annual Arithmetic Mean	_		0.030 ppm (for certain areas) ¹¹	_		
	30 Day Average	1.5 µg/m³		-	_		
Lead ^{12,13}	Calendar Quarter	_	Atomic Absorption	1.5 μg/m ³ (for certain areas) ¹²	Same as	High Volume Sampler and Atomic Absorption	
	Rolling 3-Month Average	Ι		0.15 µg/m³	Primary Standard		
Visibility Reducing Particles ¹⁴	8 Hour	See footnote 14	Beta Attenuation and Transmittance through Filter Tape	No			
Sulfates	24 Hour	25 µg/m ³	Ion Chromatography	y National			
Hydrogen Sulfide	1 Hour	0.03 ppm (42 µg/m ³)	Ultraviolet Fluorescence	Standards			
Vinyl Chloride ¹²	24 Hour	0.01 ppm (26 µg/m ³)	Gas Chromatography	hy			
See footnotes of	on next page						

For more information please call ARB-PIO at (916) 322-2990

California Air Resources Board (5/4/16)

Table 1 (continued)

- California standards for ozone, carbon monoxide (except 8-hour Lake Tahoe), sulfur dioxide (1 and 24 hour), nitrogen dioxide, and
 particulate matter (PM10, PM2.5, and visibility reducing particles), are values that are not to be exceeded. All others are not to be
 equaled or exceeded. California ambient air quality standards are listed in the Table of Standards in Section 70200 of Title 17 of the
 California Code of Regulations.
- 2. National standards (other than ozone, particulate matter, and those based on annual arithmetic mean) are not to be exceeded more than once a year. The ozone standard is attained when the fourth highest 8-hour concentration measured at each site in a year, averaged over three years, is equal to or less than the standard. For PM10, the 24 hour standard is attained when the expected number of days per calendar year with a 24-hour average concentration above 150 µg/m³ is equal to or less than one. For PM2.5, the 24 hour standard is attained when 98 percent of the daily concentrations, averaged over three years, are equal to or less than the standard. Contact the U.S. EPA for further clarification and current national policies.
- 3. Concentration expressed first in units in which it was promulgated. Equivalent units given in parentheses are based upon a reference temperature of 25°C and a reference pressure of 760 torr. Most measurements of air quality are to be corrected to a reference temperature of 25°C and a reference pressure of 760 torr; ppm in this table refers to ppm by volume, or micromoles of pollutant per mole of gas.
- 4. Any equivalent measurement method which can be shown to the satisfaction of the ARB to give equivalent results at or near the level of the air quality standard may be used.
- 5. National Primary Standards: The levels of air quality necessary, with an adequate margin of safety to protect the public health.
- National Secondary Standards: The levels of air quality necessary to protect the public welfare from any known or anticipated adverse effects of a pollutant.
- Reference method as described by the U.S. EPA. An "equivalent method" of measurement may be used but must have a "consistent relationship to the reference method" and must be approved by the U.S. EPA.
- 8. On October 1, 2015, the national 8-hour ozone primary and secondary standards were lowered from 0.075 to 0.070 ppm.
- 9. On December 14, 2012, the national annual PM2.5 primary standard was lowered from 15 μg/m³ to 12.0 μg/m³. The existing national 24-hour PM2.5 standards (primary and secondary) were retained at 35 μg/m³, as was the annual secondary standard of 15 μg/m³. The existing 24-hour PM10 standards (primary and secondary) of 150 μg/m³ also were retained. The form of the annual primary and secondary standards is the annual mean, averaged over 3 years.
- 10. To attain the 1-hour national standard, the 3-year average of the annual 98th percentile of the 1-hour daily maximum concentrations at each site must not exceed 100 ppb. Note that the national 1-hour standard is in units of parts per billion (ppb). California standards are in units of parts per million (ppm). To directly compare the national 1-hour standard to the California standards the units can be converted from ppb to ppm. In this case, the national standard of 100 ppb is identical to 0.100 ppm.
- 11. On June 2, 2010, a new 1-hour SO₂ standard was established and the existing 24-hour and annual primary standards were revoked. To attain the 1-hour national standard, the 3-year average of the annual 99th percentile of the 1-hour daily maximum concentrations at each site must not exceed 75 ppb. The 1971 SO₂ national standards (24-hour and annual) remain in effect until one year after an area is designated for the 2010 standard, except that in areas designated nonattainment for the 1971 standards, the 1971 standards remain in effect until implementation plans to attain or maintain the 2010 standards are approved.

Note that the 1-hour national standard is in units of parts per billion (ppb). California standards are in units of parts per million (ppm). To directly compare the 1-hour national standard to the California standard the units can be converted to ppm. In this case, the national standard of 75 ppb is identical to 0.075 ppm.

- 12. The ARB has identified lead and vinyl chloride as 'toxic air contaminants' with no threshold level of exposure for adverse health effects determined. These actions allow for the implementation of control measures at levels below the ambient concentrations specified for these pollutants.
- 13. The national standard for lead was revised on October 15, 2008 to a rolling 3-month average. The 1978 lead standard (1.5 μg/m³ as a quarterly average) remains in effect until one year after an area is designated for the 2008 standard, except that in areas designated nonattainment for the 1978 standard, the 1978 standard remains in effect until implementation plans to attain or maintain the 2008 standard are approved.
- 14. In 1989, the ARB converted both the general statewide 10-mile visibility standard and the Lake Tahoe 30-mile visibility standard to instrumental equivalents, which are "extinction of 0.23 per kilometer" and "extinction of 0.07 per kilometer" for the statewide and Lake Tahoe Air Basin standards, respectively.

For more information please call ARB-PIO at (916) 322-2990

California Air Resources Board (5/4/16)

Pollutants	Sources	Primary Effects
Carbon Monoxide (CO)	 Incomplete combustion of fuels and other carbon-containing substances, such as motor exhaust. Natural events, such as decomposition of organic matter. 	 Reduced tolerance for exercise. Impairment of mental function. Impairment of fetal development. Death at high levels of exposure. Aggravation of some heart diseases (angina).
Nitrogen Dioxide (NO ₂)	 Motor vehicle exhaust. High temperature stationary combustion. Atmospheric reactions. 	 Aggravation of respiratory illness. Reduced visibility. Reduced plant growth. Formation of acid rain.
Ozone (O ₃)	Atmospheric reaction of organic gases with nitrogen oxides in sunlight.	 Aggravation of respiratory and cardiovascular diseases. Irritation of eyes. Impairment of cardiopulmonary function. Plant leaf injury.
Lead (Pb)	Contaminated soil.	 Impairment of blood function and nerve construction. Behavioral and hearing problems in children.
Respirable Particulate Matter (PM-10)	 Stationary combustion of solid fuels. Construction activities. Industrial processes. Atmospheric chemical reactions. 	 Reduced lung function. Aggravation of the effects of gaseous pollutants. Aggravation of respiratory and cardio respiratory diseases. Increased cough and chest discomfort. Soiling. Reduced visibility.
Fine Particulate Matter (PM-2.5)	 Fuel combustion in motor vehicles, equipment, and industrial sources. Residential and agricultural burning. Industrial processes. Also, formed from photochemical reactions of other pollutants, including NOx, sulfur oxides, and organics. 	 Increases respiratory disease. Lung damage. Cancer and premature death. Reduces visibility and results in surface soiling.
Sulfur Dioxide (SO ₂)	 Combustion of sulfur-containing fossil fuels. Smelting of sulfur-bearing metal ores. Industrial processes. 	 Aggravation of respiratory diseases (asthma, emphysema). Reduced lung function. Irritation of eyes. Reduced visibility. Plant injury. Deterioration of metals, textiles, leather, finishes, coatings, etc.

Table 2Health Effects of Major Criteria Pollutants

Source: California Air Resources Board, 2002.

Evaluation of the most current data on the health effects of inhalation of fine particulate matter prompted the California Air Resources Board (ARB) to recommend adoption of the statewide PM-2.5 standard that is more stringent than the federal standard. This standard was adopted in 2002. The State PM-2.5 standard is more of a goal in that it does not have specific attainment planning requirements like a federal clean air standard, but only requires continued progress towards attainment.

Similarly, the ARB extensively evaluated health effects of ozone exposure. A new state standard for an 8-hour ozone exposure was adopted in 2005, which aligned with the exposure period for the federal 8-hour standard. The California 8-hour ozone standard of 0.07 ppm is more stringent than the federal 8-hour standard of 0.075 ppm. The state standard, however, does not have a specific attainment deadline. California air quality jurisdictions are required to make steady progress towards attaining state standards, but there are no hard deadlines or any consequences of non-attainment. During the same re-evaluation process, the ARB adopted an annual state standard for nitrogen dioxide (NO_2) that is more stringent than the corresponding federal standard, and strengthened the state one-hour NO_2 standard.

As part of EPA's 2002 consent decree on clean air standards, a further review of airborne particulate matter (PM) and human health was initiated. A substantial modification of federal clean air standards for PM was promulgated in 2006. Standards for PM-2.5 were strengthened, a new class of PM in the 2.5 to 10 micron size was created, some PM-10 standards were revoked, and a distinction between rural and urban air quality was adopted. In December, 2012, the federal annual standard for PM-2.5 was reduced from 15 μ g/m³ to 12 μ g/m³ which matches the California AAQS. The severity of the basin's non-attainment status for PM-2.5 may be increased by this action and thus require accelerated planning for future PM-2.5 attainment.

In response to continuing evidence that ozone exposure at levels just meeting federal clean air standards is demonstrably unhealthful, EPA had proposed a further strengthening of the 8-hour standard. A new 8-hour ozone standard was adopted in 2015 after extensive analysis and public input. The adopted national 8-hour ozone standard is 0.07 ppm which matches the current California standard. It will require three years of ambient data collection, then 2 years of non-attainment findings and planning protocol adoption, then several years of plan development and approval. Final air quality plans for the new standard are likely to be adopted around 2022. Ultimate attainment of the new standard in ozone problem areas such as Southern California might be after 2025.

In 2010 a new federal one-hour primary standard for nitrogen dioxide (NO₂) was adopted. This standard is more stringent than the existing state standard. Based upon air quality monitoring data in the South Coast Air Basin, the California Air Resources Board has requested the EPA to designate the basin as being in attainment for this standard. The federal standard for sulfur dioxide (SO₂) was also recently revised. However, with minimal combustion of coal and mandatory use of low sulfur fuels in California, SO₂ is typically not a problem pollutant.

BASELINE AIR QUALITY

Existing and probable future levels of air quality in La Mirada can be best inferred from ambient air quality measurements conducted by the South Coast Air Quality Management District (SCAQMD) at its La Habra and/or Anaheim air monitoring stations. These stations measure both regional pollution levels such as Ozone, Carbon Monoxide, Nitrogen Dioxide and PM-2.5 dust (particulates). Table 3 summarizes the last five years of monitoring data from a composite of these data resources. The following conclusions can be drawn from this data:

- a. Photochemical smog (ozone) levels occasionally exceed standards. The 8-hour state ozone standard, the 1-hour state standard as well as the 8-hour federal standard have been exceeded approximately one to two percent of all days in the past five years. Ozone data from 2014 shows some minor "back-sliding" from more than a decade of progress. While ozone levels are still high, they are much lower than 10 to 20 years ago. Attainment of all clean air standards in the project vicinity is not likely to occur soon, but the severity and frequency of violations is expected to continue to slowly decline during the current decade
- b. Measurements of carbon monoxide have shown very low baseline levels in comparison to the most stringent one- and eight-hour standards.
- c. Respirable dust (PM-10) levels exceed the state standard on approximately two percent of measurement days, but the less stringent federal PM-10 standard has not been violated once for the same period. Year to year fluctuations of overall maximum 24-hour PM-10 levels seem to follow no discernable trend, though 2015 had the lowest maximum 24-hour concentration in recent history.
- d. A substantial fraction of PM-10 is comprised of ultra-small diameter particulates capable of being inhaled into deep lung tissue (PM-2.5). Year 2013 showed the fewest violations in recent years. Both the frequency of violations of particulate standards, as well as high percentage of PM-2.5, are occasional air quality concerns in the project area. However, less than one percent of all days exceeded the current national 24-hour standard of 35 μ g/m³ from 2010-2014.

Although complete attainment of every clean air standard is not yet imminent, extrapolation of the steady improvement trend suggests that such attainment could occur within the reasonably near future.

Table 3

Air Quality Monitoring Summary (2013-2017) (Number of Days Standards Were Exceeded, and Maximum Levels During Such Violations) (Entries shown as ratios = samples exceeding standard/samples taken)

Pollutant/Standard	2013	2014	2015	2016	2017
Ozone					
1-Hour > 0.09 ppm (S)	2	5	4	3	5
8-Hour > 0.07 ppm (S)	2	6	7	6	12
8- Hour > 0.075 ppm (F)	1	2	2	2	8
Max. 1-Hour Conc. (ppm)	0.104	0.119	0.103	0.103	0.113
Max. 8-Hour Conc. (ppm)	0.078	0.088	0.082	0.078	0.086
Carbon Monoxide					
1-Hour > 20. ppm (S)	0	0	0	0	0
1-Hour > 9. ppm (S, F)	0	0	0	0	0
Max 8-Hour Conc. (ppm)	2.2	2.1	1.6	1.5	1.7
Nitrogen Dioxide					
1-Hour > 0.18 ppm (S)	0	0	0	0	0
Max. 1-Hour Conc. (ppm)	0.085	0.084	0.058	0.060	0.076
Inhalable Particulates (PM-10)					
24-Hour > 50 μ g/m ³ (S)	1/59	2/364	11/364	3/353	17/332
24-Hour > 150 μ g/m ³ (F)	0/59	0/364	0/364	0/353	0/332
Max. 24-Hr. Conc. (µg/m ³)	77.	122.	66.	74.	128.
Ultra-Fine Particulates (PM-2.5)					
24-Hour > 35 μ g/m ³ (F)	1/331	6/344	3/295	1/349	6/305
Max. 24-Hr. Conc. (µg/m ³)	37.8	56.2	45.8	44.4	53.9

S=State Standard

F=Federal Standard

Source: South Coast AQMD La Habra Air Monitoring Station for Ozone, CO and NOx Anaheim Monitoring Station for PM-10 and PM-2.5 data: <u>www.arb.ca.gov/adam/</u>

AIR QUALITY PLANNING

The Federal Clean Air Act (1977 Amendments) required that designated agencies in any area of the nation not meeting national clean air standards must prepare a plan demonstrating the steps that would bring the area into compliance with all national standards. The SCAB could not meet the deadlines for ozone, nitrogen dioxide, carbon monoxide, or PM-10. In the SCAB, the agencies designated by the governor to develop regional air quality plans are the SCAQMD and the Southern California Association of Governments (SCAG). The two agencies first adopted an Air Quality Management Plan (AQMP) in 1979 and revised it several times as earlier attainment forecasts were shown to be overly optimistic.

The 1990 Federal Clean Air Act Amendment (CAAA) required that all states with air-sheds with "serious" or worse ozone problems submit a revision to the State Implementation Plan (SIP). Amendments to the SIP have been proposed, revised and approved over the past decade. The most current regional attainment emissions forecast for ozone precursors (ROG and NOx) and for carbon monoxide (CO) and for particulate matter are shown in Table 4. Substantial reductions in emissions of ROG, NOx and CO are forecast to continue throughout the next several decades. Unless new particulate control programs are implemented, PM-10 and PM-2.5 are forecast to slightly increase.

The Air Quality Management District (AQMD) adopted an updated clean air "blueprint" in August 2003. The 2003 Air Quality Management Plan (AQMP) was approved by the EPA in 2004. The AQMP outlined the air pollution measures needed to meet federal health-based standards for ozone by 2010 and for particulates (PM-10) by 2006. The 2003 AQMP was based upon the federal one-hour ozone standard which was revoked late in 2005 and replaced by an 8-hour federal standard. Because of the revocation of the hourly standard, a new air quality planning cycle was initiated.

With re-designation of the air basin as non-attainment for the 8-hour ozone standard, a new attainment plan was developed. This plan shifted most of the one-hour ozone standard attainment strategies to the 8-hour standard. As previously noted, the attainment date was to "slip" from 2010 to 2021. The updated attainment plan also includes strategies for ultimately meeting the federal PM-2.5 standard.

Because projected attainment by 2021 required control technologies that did not exist yet, the SCAQMD requested a voluntary "bump-up" from a "severe non-attainment" area to an "extreme non-attainment" designation for ozone. The extreme designation was to allow a longer time period for these technologies to develop. If attainment cannot be demonstrated within the specified deadline without relying on "black-box" measures, EPA would have been required to impose sanctions on the region had the bump-up request not been approved. In April 2010, the EPA approved the change in the non-attainment designation from "severe-17" to "extreme." This reclassification set a later attainment deadline (2024), but also required the air basin to adopt even more stringent emissions controls.

Pollutant	2015 ^a	2020 ^b	2025 ^b	2030 ^b
NOx	357	289	266	257
VOC	400	393	393	391
PM-10	161	165	170	172
PM-2.5	67	68	70	71

 Table 4

 South Coast Air Basin Emissions Forecasts (Emissions in tons/day)

^a2015 Base Year.

^bWith current emissions reduction programs and adopted growth forecasts. Source: California Air Resources Board, 2013 Almanac of Air Quality

In other air quality attainment plan reviews, EPA had disapproved part of the SCAB PM-2.5 attainment plan included in the AQMP. EPA stated that the current attainment plan relied on PM-2.5 control regulations that had not yet been approved or implemented. It was expected that a number of rules that were pending approval would remove the identified deficiencies. If these issues were not resolved within the next several years, federal funding sanctions for transportation projects could result. The 2012 AQMP included in the current California State Implementation Plan (SIP) was expected to remedy identified PM-2.5 planning deficiencies.

The federal Clean Air Act requires that non-attainment air basins have EPA approved attainment plans in place. This requirement includes the federal one-hour ozone standard even though that standard was revoked almost ten years ago. There was no approved attainment plan for the one-hour federal standard at the time of revocation. Through a legal quirk, the SCAQMD is now required to develop an AQMP for the long since revoked one-hour federal ozone standard. Because the current SIP for the basin contains a number of control measures for the 8-hour ozone standard that are equally effective for one-hour levels, the 2012 AQMP was believed to satisfy hourly attainment planning requirements.

AQMPs are required to be updated every three years. The 2012 AQMP was adopted in early 2013. An updated AQMP was required for completion in 2016. The 2016 AQMP was adopted by the SCAQMD Board in March, 2017, and has been submitted the California Air Resources Board for forwarding to the EPA. The 2016 AQMP acknowledges that motor vehicle emissions have been effectively controlled and that reductions in NOx, the continuing ozone problem pollutant, may need to come from major stationary sources (power plants, refineries, landfill flares, etc.) . The current attainment deadlines for all federal non-attainment pollutants are now as follows:

8-hour ozone (70 ppb)	2032
Annual PM-2.5 (12 µg/m ³)	2025
8-hour ozone (75 ppb)	2024 (old standard)
1-hour ozone (120 ppb)	2023 (rescinded standard)

24-hour PM-2.5 (35 μg/m³) 2019

The key challenge is that NOx emission levels, as a critical ozone precursor pollutant, are forecast to continue to exceed the levels that would allow the above deadlines to be met. Unless additional stringent NOx control measures are adopted and implemented, ozone attainment goals may not be met.

The proposed project does not directly relate to the AQMP in that there are no specific air quality programs or regulations governing residential development projects. Conformity with adopted plans, forecasts and programs relative to population, housing, employment and land use is the primary yardstick by which impact significance of planned growth is determined. The SCAQMD, however, while acknowledging that the AQMP is a growth-accommodating document, does not favor designating regional impacts as less-than-significant just because the proposed development is consistent with regional growth projections. Air quality impact significance for the proposed project has therefore been analyzed on a project-specific basis.

AIR QUALITY IMPACT

STANDARDS OF SIGNIFICANCE

Air quality impacts are considered "significant" if they cause clean air standards to be violated where they are currently met, or if they "substantially" contribute to an existing violation of standards. Any substantial emissions of air contaminants for which there is no safe exposure, or nuisance emissions such as dust or odors, would also be considered a significant impact.

Appendix G of the California CEQA Guidelines offers the following five tests of air quality impact significance. A project would have a potentially significant impact if it:

- a. Conflicts with or obstructs implementation of the applicable air quality plan.
- b. Violates any air quality standard or contributes substantially to an existing or projected air quality violation.
- c. Results in a cumulatively considerable net increase of any criteria pollutants for which the project region is non-attainment under an applicable federal or state ambient air quality standard (including releasing emissions which exceed quantitative thresholds for ozone precursors).
- d. Exposes sensitive receptors to substantial pollutant concentrations.
- e. Creates objectionable odors affecting a substantial number of people.

Primary Pollutants

Air quality impacts generally occur on two scales of motion. Near an individual source of emissions or a collection of sources such as a crowded intersection or parking lot, levels of those pollutants that are emitted in their already unhealthful form will be highest. Carbon monoxide (CO) is an example of such a pollutant. Primary pollutant impacts can generally be evaluated directly in comparison to appropriate clean air standards. Violations of these standards where they are currently met, or a measurable worsening of an existing or future violation, would be considered a significant impact. Many particulates, especially fugitive dust emissions, are also primary pollutants. Because of the non-attainment status of the South Coast Air Basin (SCAB) for PM-10, an aggressive dust control program is required to control fugitive dust during project construction.

Secondary Pollutants

Many pollutants, however, require time to transform from a more benign form to a more unhealthful contaminant. Their impact occurs regionally far from the source. Their incremental regional impact is minute on an individual basis and cannot be quantified except through complex photochemical computer models. Analysis of significance of such emissions is based upon a specified amount of emissions (pounds, tons, etc.) even though there is no way to translate those emissions directly into a corresponding ambient air quality impact.

Because of the chemical complexity of primary versus secondary pollutants, the SCAQMD has designated significant emissions levels as surrogates for evaluating regional air quality impact significance independent of chemical transformation processes. Projects with daily emissions that exceed any of the following emission thresholds are recommended by the SCAQMD to be considered significant under CEQA guidelines.

Table 5

Daily Emissions Thresholds						
Pollutant	Construction	Operations				
ROG	75	55				
NOx	100	55				
СО	550	550				
PM-10	150	150				
PM-2.5	55	55				
SOx	150	150				
Lead	3	3				

Source: SCAQMD CEQA Air Quality Handbook, November, 1993 Rev.

Additional Indicators

In its CEQA Handbook, the SCAQMD also states that additional indicators should be used as screening criteria to determine the need for further analysis with respect to air quality. The additional indicators are as follows:

- Project could interfere with the attainment of the federal or state ambient air quality standards by either violating or contributing to an existing or projected air quality violation
- Project could result in population increases within the regional statistical area which would be in excess of that projected in the AQMP and in other than planned locations for the project's build-out year.
- Project could generate vehicle trips that cause a CO hot spot.

CONSTRUCTION ACTIVITY IMPACTS

CalEEMod was developed by the SCAQMD to provide a model by which to calculate both construction emissions and operational emissions from a variety of land use projects. It calculates both the daily maximum and annual average emissions for criteria pollutants as well as total or annual greenhouse gas (GHG) emissions.

The project entails construction of 56 condominiums in a 3-story building on a 2.33 acre site. Estimated construction emissions were modeled using CalEEMod2016.3.2 to identify maximum daily emissions for each pollutant during project construction. Construction was modeled in CalEEMod2016.3.2 using default construction equipment and schedule for a project of this size as shown in Table 6.

Construction Activity Equipment Fleet				
Phase Name and Duration	Equipment			
Creding (Cdows)	1 Grader			
Grading (6 days)	1 Dozer			
	2 Loader/Backhoes			
	1 Crane			
Construction (220 days)	1 Loader/Backhoe			
Construction (220 days)	3 Welders			
	1 Generator Set			
	2 Forklifts			
	1 Paver			
	1 Mixer			
Paving (10 days)	1 Paving Equipment			
	1 Loader/Backhoe			
	2 Rollers			
Painting (10 days)	1 Air Compressor			

Table 6Construction Activity Equipment Fleet

Utilizing this indicated equipment fleet and durations shown in Table 6 the following worst case daily construction emissions are calculated by CalEEMod and are listed in Table 7.

	l l		<u>`</u>			
Maximal Construction Emissions	ROG	NOx	СО	SO_2	PM-10	PM-2.5
2020						
Unmitigated	36.7	21.4	17.8	0.0	7.7	4.3
Mitigated	36.7	21.4	17.8	0.0	3.7	2.3
2021						
Unmitigated	36.7	1.6	2.3	0.0	0.2	0.1
Mitigated	36.7	1.6	2.3	0.0	0.2	0.1
SCAQMD Thresholds	75	100	550	150	150	55

Table 7 Construction Activity Emissions Maximum Daily Emissions (pounds/day)

Peak daily construction activity emissions are estimated be below SCAQMD CEQA thresholds without the need for added mitigation. The only model-based mitigation measured applied for this project was watering exposed dirt surfaces three times per day to minimize the generation of fugitive dust generation during grading.

Construction equipment exhaust contains carcinogenic compounds within the diesel exhaust particulates. The toxicity of diesel exhaust is evaluated relative to a 24-hour per day, 365 days per year, 70-year lifetime exposure. The SCAQMD does not generally require the analysis of construction-related diesel emissions relative to health risk due to the short period for which the majority of diesel exhaust would occur. Health risk analyses are typically assessed over a 9-, 30-, or 70-year timeframe and not over a relatively brief construction period due to the lack of health risk associated with such a brief exposure.

LOCALIZED SIGNIFICANCE THRESHOLDS

The SCAQMD has developed analysis parameters to evaluate ambient air quality on a local level in addition to the more regional emissions-based thresholds of significance. These analysis elements are called Localized Significance Thresholds (LSTs). LSTs were developed in response to Governing Board's Environmental Justice Enhancement Initiative 1-4 and the LST methodology was provisionally adopted in October 2003 and formally approved by SCAQMD's Mobile Source Committee in February 2005.

Use of an LST analysis for a project is optional. For the proposed project, the primary source of possible LST impact would be during construction. LSTs are applicable for a sensitive receptor where it is possible that an individual could remain for 24 hours such as a residence, hospital or convalescent facility.

LSTs are only applicable to the following criteria pollutants: oxides of nitrogen (NOx), carbon monoxide (CO), and particulate matter (PM-10 and PM-2.5). LSTs represent the maximum emissions from a project that are not expected to cause or contribute to an exceedance of the most stringent applicable federal or state ambient air quality standard, and are developed based on the

ambient concentrations of that pollutant for each source receptor area and distance to the nearest sensitive receptor.

LST screening tables are available for 25, 50, 100, 200 and 500 meter source-receptor distances. For this project, there are several adjacent residential uses such that the most conservative 25 meter distance was modeled.

The SCAQMD has issued guidance on applying CalEEMod to LSTs. LST pollutant screening level concentration data is currently published for 1, 2 and 5 acre sites for varying distances. For this project, the most stringent thresholds for a 1 acre site were applied.

The following thresholds and emissions in Table 8 are therefore determined (pounds per day):

LST and Project Emissions (pounds/day)						
1.0 acre/25 meters SE LA County	СО	NOx	PM-10	PM-2.5		
LST Threshold	571	80	4	3		
Max On-Site Emissions						
Unmitigated	18	21	8	4		
Mitigated	18	21	4	2		

Table 8

CalEEMod Output in Appendix

LSTs were compared to the maximum daily construction activities. As seen in Table 8, with active dust suppression, mitigated emissions meet the LST for construction thresholds. LST impacts are less-than-significant.

Therefore, the following construction mitigation measure is necessary to ensure LST thresholds are maintained below significance thresholds:

• Exposed surfaces will be watered at least three times per day during grading activities

OPERATIONAL IMPACTS

The project would generate 410 daily trips using trip generation numbers provided in the project traffic report. Operational emissions were calculated using CalEEMod2016.3.2 for an assumed full occupancy year of 2020. The operational impacts are shown in Table 9. As shown, operational emissions will not exceed applicable SCAQMD operational emissions CEQA thresholds of significance.

	TToposeu	Uses Daily O	per acionar 1	inpacts (202	0)	
	Operational Emissions (lbs/day)					
Source	ROG	NOx	СО	SO ₂	PM-10	PM-2.5
Area	16.0	1.2	33.1	0.1	4.3	4.3
Energy	0.0	0.2	0.1	0.0	0.0	0.0
Mobile	0.8	4.0	11.1	0.0	3.0	0.8
Total	16.8	5.4	44.4	0.1	7.3	5.1
SCAQMD	55	55	550	150	150	55
Threshold	55	55	550	150	150	55
Exceeds Threshold?	No	No	No	No	No	No

Table 9Proposed Uses Daily Operational Impacts (2020)

Source: CalEEMod Output in Appendix

CONSTRUCTION EMISSIONS MINIMIZATION

Construction activities are not anticipated to cause dust emissions to exceed SCAQMD CEQA thresholds. Nevertheless, emissions minimization through enhanced dust control measures is recommended for use because of the non-attainment status of the air and proximity of residential uses. Recommended measures include:

Fugitive Dust Control

- Apply soil stabilizers or moisten inactive areas.
- Water exposed surfaces as needed to avoid visible dust leaving the construction site (typically 2-3 times/day).
- Cover all stock piles with tarps at the end of each day or as needed.
- Provide water spray during loading and unloading of earthen materials.
- Minimize in-out traffic from construction zone
- Cover all trucks hauling dirt, sand, or loose material and require all trucks to maintain at least two feet of freeboard
- Sweep streets daily if visible soil material is carried out from the construction site

Similarly, ozone precursor emissions (ROG and NOx) are calculated to be below SCAQMD CEQA thresholds. However, because of the regional non-attainment for photochemical smog, the use of reasonably available control measures for diesel exhaust is recommended. Combustion emissions control options include:

Exhaust Emissions Control

- Utilize well-tuned off-road construction equipment.
- Establish a preference for contractors using Tier 3 or better rated heavy equipment.
- Enforce 5-minute idling limits for both on-road trucks and off-road equipment.

GREENHOUSE GAS EMISSIONS

"Greenhouse gases" (so called because of their role in trapping heat near the surface of the earth) emitted by human activity are implicated in global climate change, commonly referred to as "global warming." These greenhouse gases contribute to an increase in the temperature of the earth's atmosphere by transparency to short wavelength visible sunlight, but near opacity to outgoing terrestrial long wavelength heat radiation in some parts of the infrared spectrum. The principal greenhouse gases (GHGs) are carbon dioxide, methane, nitrous oxide, ozone, and water vapor. For purposes of planning and regulation, Section 15364.5 of the California Code of Regulations defines GHGs to include carbon dioxide, methane, nitrous oxide, hydrofluorocarbons, perfluorocarbons and sulfur hexafluoride. Fossil fuel consumption in the transportation sector (onroad motor vehicles, off-highway mobile sources, and aircraft) is the single largest source of GHG emissions, accounting for approximately half of GHG emissions globally. Industrial and commercial sources are the second largest contributors of GHG emissions with about one-fourth of total emissions.

California has passed several bills and the Governor has signed at least three executive orders regarding greenhouse gases. GHG statues and executive orders (EO) include AB 32, SB 1368, EO S-03-05, EO S-20-06 and EO S-01-07.

AB 32 is one of the most significant pieces of environmental legislation that California has adopted. Among other things, it is designed to maintain California's reputation as a "national and international leader on energy conservation and environmental stewardship." It will have wide-ranging effects on California businesses and lifestyles as well as far reaching effects on other states and countries. A unique aspect of AB 32, beyond its broad and wide-ranging mandatory provisions and dramatic GHG reductions are the short time frames within which it must be implemented. Major components of the AB 32 include:

- Require the monitoring and reporting of GHG emissions beginning with sources or categories of sources that contribute the most to statewide emissions.
- Requires immediate "early action" control programs on the most readily controlled GHG sources.
- Mandates that by 2020, California's GHG emissions be reduced to 1990 levels.
- Forces an overall reduction of GHG gases in California by 25-40%, from business as usual, to be achieved by 2020.
- Must complement efforts to achieve and maintain federal and state ambient air quality standards and to reduce toxic air contaminants.

Statewide, the framework for developing the implementing regulations for AB 32 is under way. Maximum GHG reductions are expected to derive from increased vehicle fuel efficiency, from greater use of renewable energy and from increased structural energy efficiency. Additionally, through the California Climate Action Registry (CCAR now called the Climate Action Reserve), general and industry-specific protocols for assessing and reporting GHG emissions have been developed. GHG sources are categorized into direct sources (i.e. company owned) and indirect sources (i.e. not company owned). Direct sources include combustion emissions from on-and off-road mobile sources, and fugitive emissions. Indirect sources include off-site electricity generation and non-company owned mobile sources.

THRESHOLDS OF SIGNIFICANCE

In response to the requirements of SB97, the State Resources Agency developed guidelines for the treatment of GHG emissions under CEQA. These new guidelines became state laws as part of Title 14 of the California Code of Regulations in March, 2010. The CEQA Appendix G guidelines were modified to include GHG as a required analysis element. A project would have a potentially significant impact if it:

- Generates GHG emissions, directly or indirectly, that may have a significant impact on the environment, or,
- Conflicts with an applicable plan, policy or regulation adopted to reduce GHG emissions.

Section 15064.4 of the Code specifies how significance of GHG emissions is to be evaluated. The process is broken down into quantification of project-related GHG emissions, making a determination of significance, and specification of any appropriate mitigation if impacts are found to be potentially significant. At each of these steps, the new GHG guidelines afford the lead agency with substantial flexibility.

Emissions identification may be quantitative, qualitative or based on performance standards. CEQA guidelines allow the lead agency to "select the model or methodology it considers most appropriate." The most common practice for transportation/combustion GHG emissions quantification is to use a computer model such as CalEEMod, as was used in the ensuing analysis.

The significance of those emissions then must be evaluated; the selection of a threshold of significance must take into consideration what level of GHG emissions would be cumulatively considerable. The guidelines are clear that they do not support a zero net emissions threshold. If the lead agency does not have sufficient expertise in evaluating GHG impacts, it may rely on thresholds adopted by an agency with greater expertise.

On December 5, 2008 the SCAQMD Governing Board adopted an Interim quantitative GHG Significance Threshold for industrial projects where the SCAQMD is the lead agency (e.g., stationary source permit projects, rules, plans, etc.) of 10,000 Metric Tons (MT) CO₂ equivalent/year. In September 2010, the SCAQMD CEQA Significance Thresholds GHG Working Group released revisions which recommended a threshold of 3,000 MT CO₂e for all land use projects. This 3,000 MT/year recommendation has been used as a guideline for this analysis. In the absence of an adopted numerical threshold of significance, project related GHG emissions in excess of the guideline level are presumed to trigger a requirement for enhanced GHG reduction at the project level.

PROJECT RELATED GHG EMISSIONS GENERATION

Construction Activity GHG Emissions

The project is assumed to require less than two years for construction. During project construction, the CalEEMod2016.3.2 computer model predicts that the construction activities will generate the annual CO₂e emissions identified in Table 10.

	CO ₂ e
Year 2020	349.7
Year 2021	1.3
Total	351.0
Amortized	11.7

Table 10
Construction Emissions (Metric Tons CO₂e)

CalEEMod Output provided in appendix

SCAQMD GHG emissions policy from construction activities is to amortize emissions over a 30year lifetime. The amortized level is also provided. GHG impacts from construction are considered individually less-than-significant.

Project Operational GHG Emissions

The input assumptions for operational GHG emissions calculations, and the GHG conversion from consumption to annual regional CO_2e emissions are summarized in the CalEEMod2016.3.2 output files found in the appendix of this report.

The total operational and annualized construction emissions for the proposed project are identified in Table 11. The project GHG emissions are considered less-than-significant.

(Metric 1	$OIIS CO_2e)$
Consumption Source	
Area Sources	18.9
Energy Utilization	147.6
Mobile Source	609.9
Solid Waste Generation	12.9
Water Consumption	28.3
Construction	11.7
Total	829.3
Guideline Threshold	3,000

Table 11Operational Emissions
(Metric Tons CO2e)

CONSISTENCY WITH GHG PLANS, PROGRAMS AND POLICIES

The City of La Mirada has not yet developed a Greenhouse Gas Reduction Plan. The applicable GHG planning document is AB-32. As discussed above, the project is not expected to result in a significant increase in GHG emissions. As a result, the project results in GHG emissions below the recommended SCAQMD 3,000 ton threshold. Therefore, the project would not conflict with any applicable plan, policy, or regulation to reduce GHG emissions.

CALEEMOD2016.3.2 COMPUTER MODEL OUTPUT

- DAILY EMISISONS
- ANNUAL EMISSIONS

Page 1 of 27

Olson La Mirada - South Coast Air Basin, Annual

Olson La Mirada

South Coast Air Basin, Annual

1.0 Project Characteristics

1.1 Land Usage

Land Uses	Size	Metric	Lot Acreage	Floor Surface Area	Population
Condo/Townhouse	56.00	Dwelling Unit	1.23	56,000.00	160
Parking Lot	128.00	Space	1.10	51,200.00	0

1.2 Other Project Characteristics

Urbanization	Urban	Wind Speed (m/s)	2.2	Precipitation Freq (Days)	31
Climate Zone	9			Operational Year	2020
Utility Company	Southern Californ	ia Edison			
CO2 Intensity (Ib/MWhr)	702.44	CH4 Intensity (Ib/MWhr)	0.029	N2O Intensity ((Ib/MWhr)).006

1.3 User Entered Comments & Non-Default Data

Project Characteristics -

Land Use - 2.33 acre site

Construction Phase -

Vehicle Trips - 410 trips per day per traffic analysis

Construction Off-road Equipment Mitigation -

Area Mitigation -

CalEEMod Version: CalEEMod.2016.3.2

Page 2 of 27

Olson La Mirada - South Coast Air Basin, Annual

Table Name	Column Name	Default Value	New Value
tblLandUse	LotAcreage	3.50	1.23
tblLandUse	LotAcreage	1.15	1.10
tblVehicleTrips	ST_TR	5.67	7.32
tblVehicleTrips	SU_TR	4.84	7.32
tblVehicleTrips	WD_TR	5.81	7.32

2.0 Emissions Summary

Page 3 of 27

Olson La Mirada - South Coast Air Basin, Annual

2.1 Overall Construction

Unmitigated Construction

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year	tons/yr												MT	/yr		
2020	0.3558	2.2311	2.0353	4.0500e- 003	0.1055	0.1121	0.2177	0.0331	0.1072	0.1404	0.0000	348.2943	348.2943	0.0551	0.0000	349.6716
2021	0.1286	5.4700e- 003	7.8300e- 003	1.0000e- 005	4.6000e- 004	3.3000e- 004	7.9000e- 004	1.2000e- 004	3.3000e- 004	4.5000e- 004	0.0000	1.2954	1.2954	7.0000e- 005	0.0000	1.2972
Maximum	0.3558	2.2311	2.0353	4.0500e- 003	0.1055	0.1121	0.2177	0.0331	0.1072	0.1404	0.0000	348.2943	348.2943	0.0551	0.0000	349.6716

Mitigated Construction

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year					tor	ns/yr							М	T/yr		
2020	0.3558	2.2311	2.0353	4.0500e- 003	0.0936	0.1121	0.2057	0.0270	0.1072	0.1342	0.0000	348.2940	348.2940	0.0551	0.0000	349.6713
2021	0.1286	5.4700e- 003	7.8300e- 003	1.0000e- 005	4.6000e- 004	3.3000e- 004	7.9000e- 004	1.2000e- 004	3.3000e- 004	4.5000e- 004	0.0000	1.2954	1.2954	7.0000e- 005	0.0000	1.2972
Maximum	0.3558	2.2311	2.0353	4.0500e- 003	0.0936	0.1121	0.2057	0.0270	0.1072	0.1342	0.0000	348.2940	348.2940	0.0551	0.0000	349.6713
	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio-CO2	Total CO2	CH4	N20	CO2e
Percent Reduction	0.00	0.00	0.00	0.00	11.31	0.00	5.49	18.53	0.00	4.38	0.00	0.00	0.00	0.00	0.00	0.00

Page 4 of 27

Olson La Mirada - South Coast Air Basin, Annual

Quarter	Start Date	End Date	Maximum Unmitigated ROG + NOX (tons/quarter)	Maximum Mitigated ROG + NOX (tons/quarter)
1	1-1-2020	3-31-2020	0.4719	0.4719
2	4-1-2020	6-30-2020	0.7055	0.7055
3	7-1-2020	9-30-2020	0.7133	0.7133
4	10-1-2020	12-31-2020	0.6898	0.6898
5	1-1-2021	3-31-2021	0.1505	0.1505
		Highest	0.7133	0.7133

2.2 Overall Operational

Unmitigated Operational

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	is/yr							МТ	/yr		
Area	0.4251	0.0212	0.9371	9.4000e- 004		0.0567	0.0567		0.0567	0.0567	5.9483	12.3771	18.3253	0.0187	4.0000e- 004	18.9123
Energy	5.1900e- 003	0.0443	0.0189	2.8000e- 004		3.5800e- 003	3.5800e- 003		3.5800e- 003	3.5800e- 003	0.0000	146.9663	146.9663	4.9300e- 003	1.7600e- 003	147.6135
Mobile	0.1402	0.7614	1.9375	6.6100e- 003	0.5320	6.7500e- 003	0.5388	0.1426	6.3400e- 003	0.1489	0.0000	609.1028	609.1028	0.0310	0.0000	609.8789
Waste	h	,	, , , ,		,	0.0000	0.0000		0.0000	0.0000	5.2291	0.0000	5.2291	0.3090	0.0000	12.9547
Water	h	, ,		,		0.0000	0.0000		0.0000	0.0000	1.1575	23.2798	24.4374	0.1199	3.0100e- 003	28.3295
Total	0.5705	0.8270	2.8934	7.8300e- 003	0.5320	0.0670	0.5990	0.1426	0.0666	0.2091	12.3349	791.7259	804.0608	0.4835	5.1700e- 003	817.6889

Page 5 of 27

Olson La Mirada - South Coast Air Basin, Annual

2.2 Overall Operational

Mitigated Operational

	ROG	NC)x	CO	SO	2 F	Fugitive PM10	Exhaus PM10	: PN To	l10 otal	Fugitiv PM2.	e Ext 5 Pl	naust M2.5	PM2.5 Total	Bio	o- CO2	NBio- CC	2 Tota	I CO2	CH4	N	20	CO2e	
Category							to	ons/yr											MT/	/yr				
Area	0.2429	0.01	72	0.5855	1.000 00	0e- 4		4.0400e 003	- 4.04 00	00e- 03		4.0 (400e-)03	4.0400e- 003	0	.0000	13.0494	13.	0494	1.1600e 003	2.20 0	00e- 04	13.1446	1
Energy	5.1900e- 003	0.04	43	0.0189	2.800 004	0e- 4		3.5800e 003	- 3.58 0(00e- 03		3.5 (800e-)03	3.5800e 003	0	.0000	146.966	146	.9663	4.9300e 003	1.76 0	00e- 03	147.6135	;
Mobile	0.1402	0.76	514	1.9375	6.610 00	0e- 3	0.5320	6.7500e 003	- 0.5	388	0.142	6 6.3 (400e-)03	0.1489	0	.0000	609.1028	609	.1028	0.0310	0.0	000	609.8789)
Waste	n							0.0000	0.0	000		0.0	0000	0.0000	5	.2291	0.0000	5.2	2291	0.3090	0.0	000	12.9547	1
Water								0.0000	0.0	000		0.0	0000	0.0000	1	.1575	23.2798	24.	4374	0.1199	3.01 0	00e- 03	28.3295	1
Total	0.3883	0.82	29	2.5419	6.990 00	0e- 3	0.5320	0.0144	0.5	464	0.142	6 0.4	0140	0.1565	6	.3866	792.398	5 798	.7849	0.4660	4.99 0	00e- 03	811.9211	l
	ROG		NOx	x	со	SO2	2 Fu I	gitive E M10	xhaust PM10	PM1 Tota	io i al	ugitive PM2.5	Exha PM	aust P 2.5 1	M2.5 otal	Bio- (CO2 NBi	o-CO2	Total C	02 (CH4	N20) C(O2e
Percent Reduction	31.94		0.49	9 1	2.15	10.73	3	0.00	78.55	8.7	8	0.00	79	.03 2	5.16	48.2	- 22).08	0.66	3 3	8.62	3.4	3 0	.71

3.0 Construction Detail

Construction Phase

CalEEMod Version: CalEEMod.2016.3.2

Page 6 of 27

Olson La Mirada - South Coast Air Basin, Annual

Phase Number	Phase Name	Phase Type	Start Date	End Date	Num Days Week	Num Days	Phase Description
1	Grading	Grading	2/1/2020	2/10/2020	5	6	
2	Building Construction	Building Construction	2/11/2020	12/14/2020	5	220	
3	Paving	Paving	12/15/2020	12/28/2020	5	10	
4	Architectural Coating	Architectural Coating	12/29/2020	1/11/2021	5	10	

Acres of Grading (Site Preparation Phase): 0

Acres of Grading (Grading Phase): 3

Acres of Paving: 1.1

Residential Indoor: 113,400; Residential Outdoor: 37,800; Non-Residential Indoor: 0; Non-Residential Outdoor: 0; Striped Parking Area: 3,072 (Architectural Coating – sqft)

OffRoad Equipment

Page 7 of 27

Olson La Mirada - South Coast Air Basin, Annual

Phase Name	Offroad Equipment Type	Amount	Usage Hours	Horse Power	Load Factor
Architectural Coating	Air Compressors	1	6.00	78	0.48
Paving	Cement and Mortar Mixers	1	8.00	9	0.56
Building Construction	Generator Sets	1	8.00	84	0.74
Building Construction	Cranes	1	8.00	231	0.29
Building Construction	Forklifts	2	7.00	89	0.20
Paving	Pavers	1	8.00	130	0.42
Paving	Rollers	2	8.00	80	0.38
Grading	Rubber Tired Dozers	1	8.00	247	0.40
Building Construction	Tractors/Loaders/Backhoes	1	6.00	97	0.37
Grading	Tractors/Loaders/Backhoes	2	7.00	97	0.37
Paving	Tractors/Loaders/Backhoes	1	8.00	97	0.37
Grading	Graders	1	8.00	187	0.41
Paving	Paving Equipment	1	8.00	132	0.36
Building Construction	Welders	3	8.00	46	0.45

Trips and VMT

Phase Name	Offroad Equipment Count	Worker Trip Number	Vendor Trip Number	Hauling Trip Number	Worker Trip Length	Vendor Trip Length	Hauling Trip Length	Worker Vehicle Class	Vendor Vehicle Class	Hauling Vehicle Class
Architectural Coating	1	12.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Building Construction	8	62.00	14.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Grading	4	10.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Paving	6	15.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT

3.1 Mitigation Measures Construction

Water Exposed Area

Page 8 of 27

Olson La Mirada - South Coast Air Basin, Annual

3.2 Grading - 2020

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					0.0197	0.0000	0.0197	0.0101	0.0000	0.0101	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Off-Road	5.7700e- 003	0.0640	0.0298	6.0000e- 005		2.9700e- 003	2.9700e- 003		2.7300e- 003	2.7300e- 003	0.0000	5.4333	5.4333	1.7600e- 003	0.0000	5.4773
Total	5.7700e- 003	0.0640	0.0298	6.0000e- 005	0.0197	2.9700e- 003	0.0226	0.0101	2.7300e- 003	0.0128	0.0000	5.4333	5.4333	1.7600e- 003	0.0000	5.4773

Unmitigated Construction Off-Site

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							МТ	/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	1.3000e- 004	1.0000e- 004	1.1400e- 003	0.0000	3.3000e- 004	0.0000	3.3000e- 004	9.0000e- 005	0.0000	9.0000e- 005	0.0000	0.2966	0.2966	1.0000e- 005	0.0000	0.2968
Total	1.3000e- 004	1.0000e- 004	1.1400e- 003	0.0000	3.3000e- 004	0.0000	3.3000e- 004	9.0000e- 005	0.0000	9.0000e- 005	0.0000	0.2966	0.2966	1.0000e- 005	0.0000	0.2968

Page 9 of 27

Olson La Mirada - South Coast Air Basin, Annual

3.2 Grading - 2020

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					7.6700e- 003	0.0000	7.6700e- 003	3.9400e- 003	0.0000	3.9400e- 003	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Off-Road	5.7700e- 003	0.0640	0.0298	6.0000e- 005		2.9700e- 003	2.9700e- 003		2.7300e- 003	2.7300e- 003	0.0000	5.4333	5.4333	1.7600e- 003	0.0000	5.4773
Total	5.7700e- 003	0.0640	0.0298	6.0000e- 005	7.6700e- 003	2.9700e- 003	0.0106	3.9400e- 003	2.7300e- 003	6.6700e- 003	0.0000	5.4333	5.4333	1.7600e- 003	0.0000	5.4773

Mitigated Construction Off-Site

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							МТ	/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	1.3000e- 004	1.0000e- 004	1.1400e- 003	0.0000	3.3000e- 004	0.0000	3.3000e- 004	9.0000e- 005	0.0000	9.0000e- 005	0.0000	0.2966	0.2966	1.0000e- 005	0.0000	0.2968
Total	1.3000e- 004	1.0000e- 004	1.1400e- 003	0.0000	3.3000e- 004	0.0000	3.3000e- 004	9.0000e- 005	0.0000	9.0000e- 005	0.0000	0.2966	0.2966	1.0000e- 005	0.0000	0.2968

Page 10 of 27

Olson La Mirada - South Coast Air Basin, Annual

3.3 Building Construction - 2020

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							МТ	/yr		
Off-Road	0.2517	1.9177	1.6387	2.7500e- 003		0.1043	0.1043	1 1 1	0.1000	0.1000	0.0000	228.4088	228.4088	0.0464	0.0000	229.5678
Total	0.2517	1.9177	1.6387	2.7500e- 003		0.1043	0.1043		0.1000	0.1000	0.0000	228.4088	228.4088	0.0464	0.0000	229.5678

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							МТ	/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	5.2100e- 003	0.1651	0.0416	3.9000e- 004	9.7000e- 003	8.1000e- 004	0.0105	2.8000e- 003	7.7000e- 004	3.5700e- 003	0.0000	37.6757	37.6757	2.5100e- 003	0.0000	37.7386
Worker	0.0304	0.0234	0.2587	7.5000e- 004	0.0748	5.8000e- 004	0.0754	0.0199	5.4000e- 004	0.0204	0.0000	67.4245	67.4245	1.9400e- 003	0.0000	67.4731
Total	0.0356	0.1885	0.3004	1.1400e- 003	0.0845	1.3900e- 003	0.0859	0.0227	1.3100e- 003	0.0240	0.0000	105.1002	105.1002	4.4500e- 003	0.0000	105.2116

Page 11 of 27

Olson La Mirada - South Coast Air Basin, Annual

3.3 Building Construction - 2020

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	0.2517	1.9177	1.6387	2.7500e- 003		0.1043	0.1043		0.1000	0.1000	0.0000	228.4086	228.4086	0.0464	0.0000	229.5675
Total	0.2517	1.9177	1.6387	2.7500e- 003		0.1043	0.1043		0.1000	0.1000	0.0000	228.4086	228.4086	0.0464	0.0000	229.5675

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	5.2100e- 003	0.1651	0.0416	3.9000e- 004	9.7000e- 003	8.1000e- 004	0.0105	2.8000e- 003	7.7000e- 004	3.5700e- 003	0.0000	37.6757	37.6757	2.5100e- 003	0.0000	37.7386
Worker	0.0304	0.0234	0.2587	7.5000e- 004	0.0748	5.8000e- 004	0.0754	0.0199	5.4000e- 004	0.0204	0.0000	67.4245	67.4245	1.9400e- 003	0.0000	67.4731
Total	0.0356	0.1885	0.3004	1.1400e- 003	0.0845	1.3900e- 003	0.0859	0.0227	1.3100e- 003	0.0240	0.0000	105.1002	105.1002	4.4500e- 003	0.0000	105.2116
Page 12 of 27

Olson La Mirada - South Coast Air Basin, Annual

3.4 Paving - 2020

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	5.7700e- 003	0.0579	0.0590	9.0000e- 005		3.2800e- 003	3.2800e- 003		3.0300e- 003	3.0300e- 003	0.0000	7.7529	7.7529	2.4600e- 003	0.0000	7.8143
Paving	1.4400e- 003					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Total	7.2100e- 003	0.0579	0.0590	9.0000e- 005		3.2800e- 003	3.2800e- 003		3.0300e- 003	3.0300e- 003	0.0000	7.7529	7.7529	2.4600e- 003	0.0000	7.8143

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							МТ	/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	3.3000e- 004	2.6000e- 004	2.8500e- 003	1.0000e- 005	8.2000e- 004	1.0000e- 005	8.3000e- 004	2.2000e- 004	1.0000e- 005	2.2000e- 004	0.0000	0.7415	0.7415	2.0000e- 005	0.0000	0.7420
Total	3.3000e- 004	2.6000e- 004	2.8500e- 003	1.0000e- 005	8.2000e- 004	1.0000e- 005	8.3000e- 004	2.2000e- 004	1.0000e- 005	2.2000e- 004	0.0000	0.7415	0.7415	2.0000e- 005	0.0000	0.7420

Page 13 of 27

Olson La Mirada - South Coast Air Basin, Annual

3.4 Paving - 2020

Mitigated Construction On-Site

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	5.7700e- 003	0.0579	0.0590	9.0000e- 005		3.2800e- 003	3.2800e- 003		3.0300e- 003	3.0300e- 003	0.0000	7.7529	7.7529	2.4600e- 003	0.0000	7.8143
Paving	1.4400e- 003					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Total	7.2100e- 003	0.0579	0.0590	9.0000e- 005		3.2800e- 003	3.2800e- 003		3.0300e- 003	3.0300e- 003	0.0000	7.7529	7.7529	2.4600e- 003	0.0000	7.8143

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							МТ	/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	3.3000e- 004	2.6000e- 004	2.8500e- 003	1.0000e- 005	8.2000e- 004	1.0000e- 005	8.3000e- 004	2.2000e- 004	1.0000e- 005	2.2000e- 004	0.0000	0.7415	0.7415	2.0000e- 005	0.0000	0.7420
Total	3.3000e- 004	2.6000e- 004	2.8500e- 003	1.0000e- 005	8.2000e- 004	1.0000e- 005	8.3000e- 004	2.2000e- 004	1.0000e- 005	2.2000e- 004	0.0000	0.7415	0.7415	2.0000e- 005	0.0000	0.7420

Page 14 of 27

Olson La Mirada - South Coast Air Basin, Annual

3.5 Architectural Coating - 2020

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Archit. Coating	0.0547					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Off-Road	3.6000e- 004	2.5300e- 003	2.7500e- 003	0.0000		1.7000e- 004	1.7000e- 004		1.7000e- 004	1.7000e- 004	0.0000	0.3830	0.3830	3.0000e- 005	0.0000	0.3837
Total	0.0551	2.5300e- 003	2.7500e- 003	0.0000		1.7000e- 004	1.7000e- 004		1.7000e- 004	1.7000e- 004	0.0000	0.3830	0.3830	3.0000e- 005	0.0000	0.3837

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	∵/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	8.0000e- 005	6.0000e- 005	6.8000e- 004	0.0000	2.0000e- 004	0.0000	2.0000e- 004	5.0000e- 005	0.0000	5.0000e- 005	0.0000	0.1780	0.1780	1.0000e- 005	0.0000	0.1781
Total	8.0000e- 005	6.0000e- 005	6.8000e- 004	0.0000	2.0000e- 004	0.0000	2.0000e- 004	5.0000e- 005	0.0000	5.0000e- 005	0.0000	0.1780	0.1780	1.0000e- 005	0.0000	0.1781

Page 15 of 27

Olson La Mirada - South Coast Air Basin, Annual

3.5 Architectural Coating - 2020

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Archit. Coating	0.0547					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Off-Road	3.6000e- 004	2.5300e- 003	2.7500e- 003	0.0000		1.7000e- 004	1.7000e- 004		1.7000e- 004	1.7000e- 004	0.0000	0.3830	0.3830	3.0000e- 005	0.0000	0.3837
Total	0.0551	2.5300e- 003	2.7500e- 003	0.0000		1.7000e- 004	1.7000e- 004		1.7000e- 004	1.7000e- 004	0.0000	0.3830	0.3830	3.0000e- 005	0.0000	0.3837

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	8.0000e- 005	6.0000e- 005	6.8000e- 004	0.0000	2.0000e- 004	0.0000	2.0000e- 004	5.0000e- 005	0.0000	5.0000e- 005	0.0000	0.1780	0.1780	1.0000e- 005	0.0000	0.1781
Total	8.0000e- 005	6.0000e- 005	6.8000e- 004	0.0000	2.0000e- 004	0.0000	2.0000e- 004	5.0000e- 005	0.0000	5.0000e- 005	0.0000	0.1780	0.1780	1.0000e- 005	0.0000	0.1781

Page 16 of 27

Olson La Mirada - South Coast Air Basin, Annual

3.5 Architectural Coating - 2021

Unmitigated Construction On-Site

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Archit. Coating	0.1276					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Off-Road	7.7000e- 004	5.3400e- 003	6.3600e- 003	1.0000e- 005		3.3000e- 004	3.3000e- 004		3.3000e- 004	3.3000e- 004	0.0000	0.8936	0.8936	6.0000e- 005	0.0000	0.8952
Total	0.1284	5.3400e- 003	6.3600e- 003	1.0000e- 005		3.3000e- 004	3.3000e- 004		3.3000e- 004	3.3000e- 004	0.0000	0.8936	0.8936	6.0000e- 005	0.0000	0.8952

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							МТ	'/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	1.7000e- 004	1.3000e- 004	1.4700e- 003	0.0000	4.6000e- 004	0.0000	4.6000e- 004	1.2000e- 004	0.0000	1.3000e- 004	0.0000	0.4018	0.4018	1.0000e- 005	0.0000	0.4021
Total	1.7000e- 004	1.3000e- 004	1.4700e- 003	0.0000	4.6000e- 004	0.0000	4.6000e- 004	1.2000e- 004	0.0000	1.3000e- 004	0.0000	0.4018	0.4018	1.0000e- 005	0.0000	0.4021

Page 17 of 27

Olson La Mirada - South Coast Air Basin, Annual

3.5 Architectural Coating - 2021

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							МТ	/yr		
Archit. Coating	0.1276					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Off-Road	7.7000e- 004	5.3400e- 003	6.3600e- 003	1.0000e- 005		3.3000e- 004	3.3000e- 004		3.3000e- 004	3.3000e- 004	0.0000	0.8936	0.8936	6.0000e- 005	0.0000	0.8952
Total	0.1284	5.3400e- 003	6.3600e- 003	1.0000e- 005		3.3000e- 004	3.3000e- 004		3.3000e- 004	3.3000e- 004	0.0000	0.8936	0.8936	6.0000e- 005	0.0000	0.8952

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							МТ	7/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	1.7000e- 004	1.3000e- 004	1.4700e- 003	0.0000	4.6000e- 004	0.0000	4.6000e- 004	1.2000e- 004	0.0000	1.3000e- 004	0.0000	0.4018	0.4018	1.0000e- 005	0.0000	0.4021
Total	1.7000e- 004	1.3000e- 004	1.4700e- 003	0.0000	4.6000e- 004	0.0000	4.6000e- 004	1.2000e- 004	0.0000	1.3000e- 004	0.0000	0.4018	0.4018	1.0000e- 005	0.0000	0.4021

4.0 Operational Detail - Mobile

Page 18 of 27

Olson La Mirada - South Coast Air Basin, Annual

4.1 Mitigation Measures Mobile

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Mitigated	0.1402	0.7614	1.9375	6.6100e- 003	0.5320	6.7500e- 003	0.5388	0.1426	6.3400e- 003	0.1489	0.0000	609.1028	609.1028	0.0310	0.0000	609.8789
Unmitigated	0.1402	0.7614	1.9375	6.6100e- 003	0.5320	6.7500e- 003	0.5388	0.1426	6.3400e- 003	0.1489	0.0000	609.1028	609.1028	0.0310	0.0000	609.8789

4.2 Trip Summary Information

	Aver	age Daily Trip Ra	ate	Unmitigated	Mitigated
Land Use	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
Condo/Townhouse	409.92	409.92	409.92	1,400,759	1,400,759
Parking Lot	0.00	0.00	0.00		
Total	409.92	409.92	409.92	1,400,759	1,400,759

4.3 Trip Type Information

		Miles			Trip %			Trip Purpos	e %
Land Use	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW	Primary	Diverted	Pass-by
Condo/Townhouse	14.70	5.90	8.70	40.20	19.20	40.60	86	11	3
Parking Lot	16.60	8.40	6.90	0.00	0.00	0.00	0	0	0

4.4 Fleet Mix

Page 19 of 27

Olson La Mirada - South Coast Air Basin, Annual

Land Use	LDA	LDT1	LDT2	MDV	LHD1	LHD2	MHD	HHD	OBUS	UBUS	MCY	SBUS	MH
Condo/Townhouse	0.550339	0.043800	0.200255	0.122233	0.016799	0.005871	0.020633	0.029727	0.002027	0.001932	0.004726	0.000704	0.000955
Parking Lot	0.550339	0.043800	0.200255	0.122233	0.016799	0.005871	0.020633	0.029727	0.002027	0.001932	0.004726	0.000704	0.000955

5.0 Energy Detail

Historical Energy Use: N

5.1 Mitigation Measures Energy

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							МТ	/yr		
Electricity Mitigated			, , ,			0.0000	0.0000		0.0000	0.0000	0.0000	95.6363	95.6363	3.9500e- 003	8.2000e- 004	95.9785
Electricity Unmitigated	Pi					0.0000	0.0000		0.0000	0.0000	0.0000	95.6363	95.6363	3.9500e- 003	8.2000e- 004	95.9785
NaturalGas Mitigated	5.1900e- 003	0.0443	0.0189	2.8000e- 004		3.5800e- 003	3.5800e- 003		3.5800e- 003	3.5800e- 003	0.0000	51.3300	51.3300	9.8000e- 004	9.4000e- 004	51.6350
NaturalGas Unmitigated	5.1900e- 003	0.0443	0.0189	2.8000e- 004		3.5800e- 003	3.5800e- 003		3.5800e- 003	3.5800e- 003	0.0000	51.3300	51.3300	9.8000e- 004	9.4000e- 004	51.6350

Page 20 of 27

Olson La Mirada - South Coast Air Basin, Annual

5.2 Energy by Land Use - NaturalGas

<u>Unmitigated</u>

	NaturalGa s Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr					ton	s/yr							MT	/yr		
Condo/Townhous e	961887	5.1900e- 003	0.0443	0.0189	2.8000e- 004		3.5800e- 003	3.5800e- 003	1 1 1	3.5800e- 003	3.5800e- 003	0.0000	51.3300	51.3300	9.8000e- 004	9.4000e- 004	51.6350
Parking Lot	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Total		5.1900e- 003	0.0443	0.0189	2.8000e- 004		3.5800e- 003	3.5800e- 003		3.5800e- 003	3.5800e- 003	0.0000	51.3300	51.3300	9.8000e- 004	9.4000e- 004	51.6350

Mitigated

	NaturalGa s Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr					ton	s/yr							MT	/yr		
Condo/Townhous e	961887	5.1900e- 003	0.0443	0.0189	2.8000e- 004		3.5800e- 003	3.5800e- 003		3.5800e- 003	3.5800e- 003	0.0000	51.3300	51.3300	9.8000e- 004	9.4000e- 004	51.6350
Parking Lot	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Total		5.1900e- 003	0.0443	0.0189	2.8000e- 004		3.5800e- 003	3.5800e- 003		3.5800e- 003	3.5800e- 003	0.0000	51.3300	51.3300	9.8000e- 004	9.4000e- 004	51.6350

Page 21 of 27

Olson La Mirada - South Coast Air Basin, Annual

5.3 Energy by Land Use - Electricity

<u>Unmitigated</u>

	Electricity Use	Total CO2	CH4	N2O	CO2e
Land Use	kWh/yr		МТ	/yr	
Condo/Townhous e	282237	89.9266	3.7100e- 003	7.7000e- 004	90.2484
Parking Lot	17920	5.7097	2.4000e- 004	5.0000e- 005	5.7301
Total		95.6363	3.9500e- 003	8.2000e- 004	95.9785

Mitigated

	Electricity Use	Total CO2	CH4	N2O	CO2e
Land Use	kWh/yr		МТ	/yr	
Condo/Townhous e	282237	89.9266	3.7100e- 003	7.7000e- 004	90.2484
Parking Lot	17920	5.7097	2.4000e- 004	5.0000e- 005	5.7301
Total		95.6363	3.9500e- 003	8.2000e- 004	95.9785

6.0 Area Detail

6.1 Mitigation Measures Area

CalEEMod Version: CalEEMod.2016.3.2

Page 22 of 27

Olson La Mirada - South Coast Air Basin, Annual

Use only Natural Gas Hearths

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							МТ	/yr		
Mitigated	0.2429	0.0172	0.5855	1.0000e- 004		4.0400e- 003	4.0400e- 003		4.0400e- 003	4.0400e- 003	0.0000	13.0494	13.0494	1.1600e- 003	2.2000e- 004	13.1446
Unmitigated	0.4251	0.0212	0.9371	9.4000e- 004		0.0567	0.0567	 - - - -	0.0567	0.0567	5.9483	12.3771	18.3253	0.0187	4.0000e- 004	18.9123

6.2 Area by SubCategory

<u>Unmitigated</u>

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory					ton	s/yr							MT	ī/yr		
Architectural Coating	0.0182					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Consumer Products	0.2057	, , ,				0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Hearth	0.1834	0.0145	0.3560	9.1000e- 004		0.0535	0.0535		0.0535	0.0535	5.9483	11.4305	17.3788	0.0177	4.0000e- 004	17.9426
Landscaping	0.0178	6.7200e- 003	0.5811	3.0000e- 005		3.1900e- 003	3.1900e- 003		3.1900e- 003	3.1900e- 003	0.0000	0.9465	0.9465	9.3000e- 004	0.0000	0.9697
Total	0.4251	0.0212	0.9371	9.4000e- 004		0.0567	0.0567		0.0567	0.0567	5.9483	12.3771	18.3253	0.0187	4.0000e- 004	18.9123

Page 23 of 27

Olson La Mirada - South Coast Air Basin, Annual

6.2 Area by SubCategory

Mitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory					ton	s/yr							MT	ī/yr		
Architectural Coating	0.0182					0.0000	0.0000	1 1 1	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Consumer Products	0.2057					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Hearth	1.2200e- 003	0.0105	4.4500e- 003	7.0000e- 005		8.4000e- 004	8.4000e- 004		8.4000e- 004	8.4000e- 004	0.0000	12.1029	12.1029	2.3000e- 004	2.2000e- 004	12.1748
Landscaping	0.0178	6.7200e- 003	0.5811	3.0000e- 005		3.1900e- 003	3.1900e- 003		3.1900e- 003	3.1900e- 003	0.0000	0.9465	0.9465	9.3000e- 004	0.0000	0.9697
Total	0.2429	0.0172	0.5855	1.0000e- 004		4.0300e- 003	4.0300e- 003		4.0300e- 003	4.0300e- 003	0.0000	13.0494	13.0494	1.1600e- 003	2.2000e- 004	13.1446

7.0 Water Detail

7.1 Mitigation Measures Water

Page 24 of 27

Olson La Mirada - South Coast Air Basin, Annual

	Total CO2	CH4	N2O	CO2e
Category		MT	ī/yr	
Mitigated	24.4374	0.1199	3.0100e- 003	28.3295
Unmitigated	24.4374	0.1199	3.0100e- 003	28.3295

7.2 Water by Land Use

<u>Unmitigated</u>

	Indoor/Out door Use	Total CO2	CH4	N2O	CO2e
Land Use	Mgal		MT	√yr	
Condo/Townhous e	3.64863 / 2.30022	24.4374	0.1199	3.0100e- 003	28.3295
Parking Lot	0/0	0.0000	0.0000	0.0000	0.0000
Total		24.4374	0.1199	3.0100e- 003	28.3295

CalEEMod Version: CalEEMod.2016.3.2

Page 25 of 27

Olson La Mirada - South Coast Air Basin, Annual

7.2 Water by Land Use

Mitigated

	Indoor/Out door Use	Total CO2	CH4	N2O	CO2e
Land Use	Mgal		M	/yr	
Condo/Townhous e	3.64863 / 2.30022	24.4374	0.1199	3.0100e- 003	28.3295
Parking Lot	0/0	0.0000	0.0000	0.0000	0.0000
Total		24.4374	0.1199	3.0100e- 003	28.3295

8.0 Waste Detail

8.1 Mitigation Measures Waste

Category/Year

	Total CO2	CH4	N2O	CO2e
		MT	/yr	
Mitigated	5.2291	0.3090	0.0000	12.9547
Unmitigated	5.2291	0.3090	0.0000	12.9547

Page 26 of 27

Olson La Mirada - South Coast Air Basin, Annual

8.2 Waste by Land Use

<u>Unmitigated</u>

	Waste Disposed	Total CO2	CH4	N2O	CO2e
Land Use	tons		МТ	/yr	
Condo/Townhous e	25.76	5.2291	0.3090	0.0000	12.9547
Parking Lot	0	0.0000	0.0000	0.0000	0.0000
Total		5.2291	0.3090	0.0000	12.9547

Mitigated

	Waste Disposed	Total CO2	CH4	N2O	CO2e
Land Use	tons		MT	/yr	
Condo/Townhous e	25.76	5.2291	0.3090	0.0000	12.9547
Parking Lot	0	0.0000	0.0000	0.0000	0.0000
Total		5.2291	0.3090	0.0000	12.9547

9.0 Operational Offroad

Hours/Day

Page 27 of 27

Olson La Mirada - South Coast Air Basin, Annual

10.0 Stationary Equipment

Fire Pumps and Emergency Generators

Equipment Type	Number	Hours/Day	Hours/Year	Horse Power	Load Factor	Fuel Type

Boilers

Equipment Type	Number	Heat Input/Day	Heat Input/Year	Boiler Rating	Fuel Type

User Defined Equipment

|--|

11.0 Vegetation

Page 1 of 22

Olson La Mirada - South Coast Air Basin, Summer

Olson La Mirada

South Coast Air Basin, Summer

1.0 Project Characteristics

1.1 Land Usage

Land Uses	Size	Metric	Lot Acreage	Floor Surface Area	Population
Condo/Townhouse	56.00	Dwelling Unit	1.23	56,000.00	160
Parking Lot	128.00	Space	1.10	51,200.00	0

1.2 Other Project Characteristics

Urbanization	Urban	Wind Speed (m/s)	2.2	Precipitation Freq (Days)	31
Climate Zone	9			Operational Year	2020
Utility Company	Southern Californ	ia Edison			
CO2 Intensity (Ib/MWhr)	702.44	CH4 Intensity (Ib/MWhr)	0.029	N2O Intensity ((Ib/MWhr)).006

1.3 User Entered Comments & Non-Default Data

Project Characteristics -

Land Use - 2.33 acre site

Construction Phase -

Vehicle Trips - 410 trips per day per traffic analysis

Construction Off-road Equipment Mitigation -

Area Mitigation -

CalEEMod Version: CalEEMod.2016.3.2

Page 2 of 22

Olson La Mirada - South Coast Air Basin, Summer

Table Name	Column Name	Default Value	New Value
tblLandUse	LotAcreage	3.50	1.23
tblLandUse	LotAcreage	1.15	1.10
tblVehicleTrips	ST_TR	5.67	7.32
tblVehicleTrips	SU_TR	4.84	7.32
tblVehicleTrips	WD_TR	5.81	7.32

2.0 Emissions Summary

Page 3 of 22

Olson La Mirada - South Coast Air Basin, Summer

2.1 Overall Construction (Maximum Daily Emission)

Unmitigated Construction

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year					lb/o	day							lb/c	lay		
2020	36.7605	21.3721	17.7828	0.0357	6.6641	0.9910	7.6551	3.3971	0.9207	4.3089	0.0000	3,379.974 1	3,379.974 1	0.6490	0.0000	3,392.709 8
2021	36.7336	1.5596	2.2681	4.3000e- 003	0.1341	0.0951	0.2292	0.0356	0.0950	0.1306	0.0000	414.2758	414.2758	0.0229	0.0000	414.8482
Maximum	36.7605	21.3721	17.7828	0.0357	6.6641	0.9910	7.6551	3.3971	0.9207	4.3089	0.0000	3,379.974 1	3,379.974 1	0.6490	0.0000	3,392.709 8

Mitigated Construction

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year					lb/	′day							lb/	day		
2020	36.7605	21.3721	17.7828	0.0357	2.6672	0.9910	3.6582	1.3430	0.9207	2.2547	0.0000	3,379.974 1	3,379.974 1	0.6490	0.0000	3,392.709 8
2021	36.7336	1.5596	2.2681	4.3000e- 003	0.1341	0.0951	0.2292	0.0356	0.0950	0.1306	0.0000	414.2758	414.2758	0.0229	0.0000	414.8482
Maximum	36.7605	21.3721	17.7828	0.0357	2.6672	0.9910	3.6582	1.3430	0.9207	2.2547	0.0000	3,379.974 1	3,379.974 1	0.6490	0.0000	3,392.709 8
	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio-CO2	Total CO2	CH4	N20	CO2e
Percent Reduction	0.00	0.00	0.00	0.00	58.79	0.00	50.69	59.84	0.00	46.27	0.00	0.00	0.00	0.00	0.00	0.00

Page 4 of 22

Olson La Mirada - South Coast Air Basin, Summer

2.2 Overall Operational

Unmitigated Operational

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/c	lay							lb/c	lay		
Area	16.0432	1.2156	33.1275	0.0729		4.3033	4.3033		4.3033	4.3033	524.5474	1,016.346 9	1,540.894 4	1.5725	0.0356	1,590.816 2
Energy	0.0284	0.2429	0.1034	1.5500e- 003		0.0196	0.0196		0.0196	0.0196		310.0362	310.0362	5.9400e- 003	5.6800e- 003	311.8786
Mobile	0.8201	4.0035	11.1424	0.0378	2.9771	0.0371	3.0142	0.7965	0.0348	0.8313		3,837.425 8	3,837.425 8	0.1897		3,842.169 2
Total	16.8918	5.4620	44.3732	0.1122	2.9771	4.3600	7.3371	0.7965	4.3577	5.1542	524.5474	5,163.809 0	5,688.356 4	1.7682	0.0413	5,744.863 9

Mitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/	day							lb/d	day		
Area	1.4671	0.8898	5.0044	5.5800e- 003		0.0931	0.0931		0.0931	0.0931	0.0000	1,075.6411	1,075.6411	0.0286	0.0196	1,082.188 1
Energy	0.0284	0.2429	0.1034	1.5500e- 003		0.0196	0.0196	 , , , ,	0.0196	0.0196		310.0362	310.0362	5.9400e- 003	5.6800e- 003	311.8786
Mobile	0.8201	4.0035	11.1424	0.0378	2.9771	0.0371	3.0142	0.7965	0.0348	0.8313		3,837.425 8	3,837.425 8	0.1897	1	3,842.169 2
Total	2.3156	5.1361	16.2501	0.0449	2.9771	0.1498	3.1270	0.7965	0.1476	0.9441	0.0000	5,223.103 1	5,223.103 1	0.2243	0.0253	5,236.235 9

Olson La Mirada - South Coast Air Basin, Summer

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio-CO2	Total CO2	CH4	N20	CO2e
Percent Reduction	86.29	5.97	63.38	59.98	0.00	96.56	57.38	0.00	96.61	81.68	100.00	-1.15	8.18	87.31	38.83	8.85

3.0 Construction Detail

Construction Phase

Phase Number	Phase Name	Phase Type	Start Date	End Date	Num Days Week	Num Days	Phase Description
1	Grading	Grading	2/1/2020	2/10/2020	5	6	
2	Building Construction	Building Construction	2/11/2020	12/14/2020	5	220	
3	Paving	Paving	12/15/2020	12/28/2020	5	10	
4	Architectural Coating	Architectural Coating	12/29/2020	1/11/2021	5	10	

Acres of Grading (Site Preparation Phase): 0

Acres of Grading (Grading Phase): 3

Acres of Paving: 1.1

Residential Indoor: 113,400; Residential Outdoor: 37,800; Non-Residential Indoor: 0; Non-Residential Outdoor: 0; Striped Parking Area: 3,072 (Architectural Coating – sqft)

OffRoad Equipment

Page 6 of 22

Olson La Mirada - South Coast Air Basin, Summer

Phase Name	Offroad Equipment Type	Amount	Usage Hours	Horse Power	Load Factor
Architectural Coating	Air Compressors	1	6.00	78	0.48
Paving	Cement and Mortar Mixers	1	8.00	9	0.56
Building Construction	Generator Sets	1	8.00	84	0.74
Building Construction	Cranes	1	8.00	231	0.29
Building Construction	Forklifts	2	7.00	89	0.20
Paving	Pavers	1	8.00	130	0.42
Paving	Rollers	2	8.00	80	0.38
Grading	Rubber Tired Dozers	1	8.00	247	0.40
Building Construction	Tractors/Loaders/Backhoes	1	6.00	97	0.37
Grading	Tractors/Loaders/Backhoes	2	7.00	97	0.37
Paving	Tractors/Loaders/Backhoes	1	8.00	97	0.37
Grading	Graders	1	8.00	187	0.41
Paving	Paving Equipment	1	8.00	132	0.36
Building Construction	Welders	3	8.00	46	0.45

Trips and VMT

Phase Name	Offroad Equipment Count	Worker Trip Number	Vendor Trip Number	Hauling Trip Number	Worker Trip Length	Vendor Trip Length	Hauling Trip Length	Worker Vehicle Class	Vendor Vehicle Class	Hauling Vehicle Class
Architectural Coating	1	12.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Building Construction	8	62.00	14.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Grading	4	10.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Paving	6	15.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT

3.1 Mitigation Measures Construction

Water Exposed Area

Page 7 of 22

Olson La Mirada - South Coast Air Basin, Summer

3.2 Grading - 2020

Unmitigated Construction On-Site

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Fugitive Dust					6.5523	0.0000	6.5523	3.3675	0.0000	3.3675			0.0000			0.0000
Off-Road	1.9219	21.3418	9.9355	0.0206		0.9902	0.9902		0.9110	0.9110		1,996.406 1	1,996.406 1	0.6457		2,012.548 0
Total	1.9219	21.3418	9.9355	0.0206	6.5523	0.9902	7.5425	3.3675	0.9110	4.2784		1,996.406 1	1,996.406 1	0.6457		2,012.548 0

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/c	day							lb/d	lay		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.0449	0.0303	0.4076	1.1500e- 003	0.1118	8.5000e- 004	0.1126	0.0296	7.9000e- 004	0.0304		114.3836	114.3836	3.3000e- 003		114.4660
Total	0.0449	0.0303	0.4076	1.1500e- 003	0.1118	8.5000e- 004	0.1126	0.0296	7.9000e- 004	0.0304		114.3836	114.3836	3.3000e- 003		114.4660

Page 8 of 22

Olson La Mirada - South Coast Air Basin, Summer

3.2 Grading - 2020

Mitigated Construction On-Site

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	lay		
Fugitive Dust					2.5554	0.0000	2.5554	1.3133	0.0000	1.3133			0.0000			0.0000
Off-Road	1.9219	21.3418	9.9355	0.0206		0.9902	0.9902		0.9110	0.9110	0.0000	1,996.406 1	1,996.406 1	0.6457		2,012.548 0
Total	1.9219	21.3418	9.9355	0.0206	2.5554	0.9902	3.5456	1.3133	0.9110	2.2243	0.0000	1,996.406 1	1,996.406 1	0.6457		2,012.548 0

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/c	lay							lb/c	day		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.0449	0.0303	0.4076	1.1500e- 003	0.1118	8.5000e- 004	0.1126	0.0296	7.9000e- 004	0.0304		114.3836	114.3836	3.3000e- 003		114.4660
Total	0.0449	0.0303	0.4076	1.1500e- 003	0.1118	8.5000e- 004	0.1126	0.0296	7.9000e- 004	0.0304		114.3836	114.3836	3.3000e- 003		114.4660

Page 9 of 22

Olson La Mirada - South Coast Air Basin, Summer

3.3 Building Construction - 2020

Unmitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/e	day							lb/c	lay		
Off-Road	2.2879	17.4336	14.8972	0.0250		0.9482	0.9482		0.9089	0.9089		2,288.887 7	2,288.887 7	0.4646		2,300.501 4
Total	2.2879	17.4336	14.8972	0.0250		0.9482	0.9482		0.9089	0.9089		2,288.887 7	2,288.887 7	0.4646		2,300.501 4

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/e	day							lb/c	day		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0465	1.4745	0.3587	3.5700e- 003	0.0896	7.3000e- 003	0.0969	0.0258	6.9800e- 003	0.0328		381.9078	381.9078	0.0244		382.5190
Worker	0.2781	0.1880	2.5270	7.1200e- 003	0.6930	5.2900e- 003	0.6983	0.1838	4.8700e- 003	0.1887		709.1785	709.1785	0.0204		709.6895
Total	0.3246	1.6625	2.8857	0.0107	0.7826	0.0126	0.7952	0.2096	0.0119	0.2214		1,091.086 4	1,091.086 4	0.0449		1,092.208 4

Page 10 of 22

Olson La Mirada - South Coast Air Basin, Summer

3.3 Building Construction - 2020

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/e	day							lb/c	lay		
Off-Road	2.2879	17.4336	14.8972	0.0250		0.9482	0.9482		0.9089	0.9089	0.0000	2,288.887 7	2,288.887 7	0.4646		2,300.501 4
Total	2.2879	17.4336	14.8972	0.0250		0.9482	0.9482		0.9089	0.9089	0.0000	2,288.887 7	2,288.887 7	0.4646		2,300.501 4

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/e	day							lb/c	day		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0465	1.4745	0.3587	3.5700e- 003	0.0896	7.3000e- 003	0.0969	0.0258	6.9800e- 003	0.0328		381.9078	381.9078	0.0244		382.5190
Worker	0.2781	0.1880	2.5270	7.1200e- 003	0.6930	5.2900e- 003	0.6983	0.1838	4.8700e- 003	0.1887		709.1785	709.1785	0.0204		709.6895
Total	0.3246	1.6625	2.8857	0.0107	0.7826	0.0126	0.7952	0.2096	0.0119	0.2214		1,091.086 4	1,091.086 4	0.0449		1,092.208 4

Page 11 of 22

Olson La Mirada - South Coast Air Basin, Summer

3.4 Paving - 2020

Unmitigated Construction On-Site

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	lay		
Off-Road	1.1547	11.5873	11.8076	0.0178		0.6565	0.6565		0.6051	0.6051		1,709.218 0	1,709.218 0	0.5417		1,722.760 5
Paving	0.2882					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Total	1.4429	11.5873	11.8076	0.0178		0.6565	0.6565		0.6051	0.6051		1,709.218 0	1,709.218 0	0.5417		1,722.760 5

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/c	Jay							lb/c	day		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.0673	0.0455	0.6114	1.7200e- 003	0.1677	1.2800e- 003	0.1689	0.0445	1.1800e- 003	0.0456		171.5755	171.5755	4.9400e- 003		171.6991
Total	0.0673	0.0455	0.6114	1.7200e- 003	0.1677	1.2800e- 003	0.1689	0.0445	1.1800e- 003	0.0456		171.5755	171.5755	4.9400e- 003		171.6991

Page 12 of 22

Olson La Mirada - South Coast Air Basin, Summer

3.4 Paving - 2020

Mitigated Construction On-Site

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	lay		
Off-Road	1.1547	11.5873	11.8076	0.0178		0.6565	0.6565		0.6051	0.6051	0.0000	1,709.218 0	1,709.218 0	0.5417		1,722.760 5
Paving	0.2882					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Total	1.4429	11.5873	11.8076	0.0178		0.6565	0.6565		0.6051	0.6051	0.0000	1,709.218 0	1,709.218 0	0.5417		1,722.760 5

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	day		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.0673	0.0455	0.6114	1.7200e- 003	0.1677	1.2800e- 003	0.1689	0.0445	1.1800e- 003	0.0456		171.5755	171.5755	4.9400e- 003		171.6991
Total	0.0673	0.0455	0.6114	1.7200e- 003	0.1677	1.2800e- 003	0.1689	0.0445	1.1800e- 003	0.0456		171.5755	171.5755	4.9400e- 003		171.6991

Page 13 of 22

Olson La Mirada - South Coast Air Basin, Summer

3.5 Architectural Coating - 2020

Unmitigated Construction On-Site

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Archit. Coating	36.4645					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Off-Road	0.2422	1.6838	1.8314	2.9700e- 003		0.1109	0.1109		0.1109	0.1109		281.4481	281.4481	0.0218		281.9928
Total	36.7067	1.6838	1.8314	2.9700e- 003		0.1109	0.1109		0.1109	0.1109		281.4481	281.4481	0.0218		281.9928

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/c	day							lb/c	day		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.0538	0.0364	0.4891	1.3800e- 003	0.1341	1.0200e- 003	0.1352	0.0356	9.4000e- 004	0.0365		137.2604	137.2604	3.9600e- 003		137.3593
Total	0.0538	0.0364	0.4891	1.3800e- 003	0.1341	1.0200e- 003	0.1352	0.0356	9.4000e- 004	0.0365		137.2604	137.2604	3.9600e- 003		137.3593

Page 14 of 22

Olson La Mirada - South Coast Air Basin, Summer

3.5 Architectural Coating - 2020

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Archit. Coating	36.4645					0.0000	0.0000		0.0000	0.0000		1 1 1	0.0000			0.0000
Off-Road	0.2422	1.6838	1.8314	2.9700e- 003		0.1109	0.1109		0.1109	0.1109	0.0000	281.4481	281.4481	0.0218		281.9928
Total	36.7067	1.6838	1.8314	2.9700e- 003		0.1109	0.1109		0.1109	0.1109	0.0000	281.4481	281.4481	0.0218		281.9928

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/e	day							lb/c	day		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.0538	0.0364	0.4891	1.3800e- 003	0.1341	1.0200e- 003	0.1352	0.0356	9.4000e- 004	0.0365		137.2604	137.2604	3.9600e- 003		137.3593
Total	0.0538	0.0364	0.4891	1.3800e- 003	0.1341	1.0200e- 003	0.1352	0.0356	9.4000e- 004	0.0365		137.2604	137.2604	3.9600e- 003		137.3593

Page 15 of 22

Olson La Mirada - South Coast Air Basin, Summer

3.5 Architectural Coating - 2021

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Archit. Coating	36.4645					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Off-Road	0.2189	1.5268	1.8176	2.9700e- 003		0.0941	0.0941		0.0941	0.0941		281.4481	281.4481	0.0193		281.9309
Total	36.6834	1.5268	1.8176	2.9700e- 003		0.0941	0.0941		0.0941	0.0941		281.4481	281.4481	0.0193		281.9309

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/e	day							lb/c	day		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.0502	0.0328	0.4506	1.3300e- 003	0.1341	9.9000e- 004	0.1351	0.0356	9.1000e- 004	0.0365		132.8278	132.8278	3.5800e- 003		132.9173
Total	0.0502	0.0328	0.4506	1.3300e- 003	0.1341	9.9000e- 004	0.1351	0.0356	9.1000e- 004	0.0365		132.8278	132.8278	3.5800e- 003		132.9173

Page 16 of 22

Olson La Mirada - South Coast Air Basin, Summer

3.5 Architectural Coating - 2021

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	day		
Archit. Coating	36.4645					0.0000	0.0000		0.0000	0.0000		1 1 1	0.0000			0.0000
Off-Road	0.2189	1.5268	1.8176	2.9700e- 003		0.0941	0.0941		0.0941	0.0941	0.0000	281.4481	281.4481	0.0193		281.9309
Total	36.6834	1.5268	1.8176	2.9700e- 003		0.0941	0.0941		0.0941	0.0941	0.0000	281.4481	281.4481	0.0193		281.9309

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/e	day							lb/c	day		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.0502	0.0328	0.4506	1.3300e- 003	0.1341	9.9000e- 004	0.1351	0.0356	9.1000e- 004	0.0365		132.8278	132.8278	3.5800e- 003		132.9173
Total	0.0502	0.0328	0.4506	1.3300e- 003	0.1341	9.9000e- 004	0.1351	0.0356	9.1000e- 004	0.0365		132.8278	132.8278	3.5800e- 003		132.9173

4.0 Operational Detail - Mobile

Page 17 of 22

Olson La Mirada - South Coast Air Basin, Summer

4.1 Mitigation Measures Mobile

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	lay		
Mitigated	0.8201	4.0035	11.1424	0.0378	2.9771	0.0371	3.0142	0.7965	0.0348	0.8313		3,837.425 8	3,837.425 8	0.1897		3,842.169 2
Unmitigated	0.8201	4.0035	11.1424	0.0378	2.9771	0.0371	3.0142	0.7965	0.0348	0.8313		3,837.425 8	3,837.425 8	0.1897		3,842.169 2

4.2 Trip Summary Information

	Aver	age Daily Trip Ra	ate	Unmitigated	Mitigated
Land Use	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
Condo/Townhouse	409.92	409.92	409.92	1,400,759	1,400,759
Parking Lot	0.00	0.00	0.00		
Total	409.92	409.92	409.92	1,400,759	1,400,759

4.3 Trip Type Information

		Miles			Trip %			Trip Purpos	e %
Land Use	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW	Primary	Diverted	Pass-by
Condo/Townhouse	14.70	5.90	8.70	40.20	19.20	40.60	86	11	3
Parking Lot	16.60	8.40	6.90	0.00	0.00	0.00	0	0	0

4.4 Fleet Mix

Page 18 of 22

Olson La Mirada - South Coast Air Basin, Summer

Land Use	LDA	LDT1	LDT2	MDV	LHD1	LHD2	MHD	HHD	OBUS	UBUS	MCY	SBUS	MH
Condo/Townhouse	0.550339	0.043800	0.200255	0.122233	0.016799	0.005871	0.020633	0.029727	0.002027	0.001932	0.004726	0.000704	0.000955
Parking Lot	0.550339	0.043800	0.200255	0.122233	0.016799	0.005871	0.020633	0.029727	0.002027	0.001932	0.004726	0.000704	0.000955

5.0 Energy Detail

Historical Energy Use: N

5.1 Mitigation Measures Energy

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	day		
NaturalGas Mitigated	0.0284	0.2429	0.1034	1.5500e- 003		0.0196	0.0196		0.0196	0.0196		310.0362	310.0362	5.9400e- 003	5.6800e- 003	311.8786
NaturalGas Unmitigated	0.0284	0.2429	0.1034	1.5500e- 003		0.0196	0.0196		0.0196	0.0196		310.0362	310.0362	5.9400e- 003	5.6800e- 003	311.8786

Page 19 of 22

Olson La Mirada - South Coast Air Basin, Summer

5.2 Energy by Land Use - NaturalGas

<u>Unmitigated</u>

	NaturalGa s Use	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr					lb/	day							lb/c	lay		
Condo/Townhous e	2635.31	0.0284	0.2429	0.1034	1.5500e- 003		0.0196	0.0196	1 1 1	0.0196	0.0196		310.0362	310.0362	5.9400e- 003	5.6800e- 003	311.8786
Parking Lot	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Total		0.0284	0.2429	0.1034	1.5500e- 003		0.0196	0.0196		0.0196	0.0196		310.0362	310.0362	5.9400e- 003	5.6800e- 003	311.8786

Mitigated

	NaturalGa s Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr					lb/e	day							lb/c	lay		
Condo/Townhous e	2.63531	0.0284	0.2429	0.1034	1.5500e- 003		0.0196	0.0196		0.0196	0.0196		310.0362	310.0362	5.9400e- 003	5.6800e- 003	311.8786
Parking Lot	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Total		0.0284	0.2429	0.1034	1.5500e- 003		0.0196	0.0196		0.0196	0.0196		310.0362	310.0362	5.9400e- 003	5.6800e- 003	311.8786

6.0 Area Detail

6.1 Mitigation Measures Area

CalEEMod Version: CalEEMod.2016.3.2

Page 20 of 22

Olson La Mirada - South Coast Air Basin, Summer

Use only Natural Gas Hearths

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e	
Category	lb/day										lb/day						
Mitigated	1.4671	0.8898	5.0044	5.5800e- 003		0.0931	0.0931		0.0931	0.0931	0.0000	1,075.6411	1,075.6411	0.0286	0.0196	1,082.188 1	
Unmitigated	16.0432	1.2156	33.1275	0.0729		4.3033	4.3033	 - - -	4.3033	4.3033	524.5474	1,016.346 9	1,540.894 4	1.5725	0.0356	1,590.816 2	

6.2 Area by SubCategory

Unmitigated

	ROG	NOx	со	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e	
SubCategory	lb/day										lb/day						
Architectural Coating	0.0999					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000	
Consumer Products	1.1269					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000	
Hearth	14.6740	1.1619	28.4789	0.0727		4.2778	4.2778		4.2778	4.2778	524.5474	1,008.000 0	1,532.547 4	1.5643	0.0356	1,582.264 5	
Landscaping	0.1424	0.0537	4.6486	2.4000e- 004		0.0255	0.0255		0.0255	0.0255		8.3469	8.3469	8.1900e- 003		8.5516	
Total	16.0433	1.2156	33.1275	0.0729		4.3033	4.3033		4.3033	4.3033	524.5474	1,016.346 9	1,540.894 4	1.5725	0.0356	1,590.816 2	
Page 21 of 22

Olson La Mirada - South Coast Air Basin, Summer

6.2 Area by SubCategory

Mitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory	lb/day								lb/day							
Architectural Coating	0.0999					0.0000	0.0000	1 1 1	0.0000	0.0000			0.0000			0.0000
Consumer Products	1.1269					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Hearth	0.0978	0.8361	0.3558	5.3400e- 003		0.0676	0.0676		0.0676	0.0676	0.0000	1,067.294 1	1,067.294 1	0.0205	0.0196	1,073.636 5
Landscaping	0.1424	0.0537	4.6486	2.4000e- 004		0.0255	0.0255		0.0255	0.0255		8.3469	8.3469	8.1900e- 003		8.5516
Total	1.4671	0.8898	5.0043	5.5800e- 003		0.0931	0.0931		0.0931	0.0931	0.0000	1,075.641 1	1,075.641 1	0.0287	0.0196	1,082.188 1

7.0 Water Detail

7.1 Mitigation Measures Water

8.0 Waste Detail

8.1 Mitigation Measures Waste

9.0 Operational Offroad

Equipment Type	Number	Hours/Day	Days/Year	Horse Power	Load Factor	Fuel Type
----------------	--------	-----------	-----------	-------------	-------------	-----------

10.0 Stationary Equipment

Page 22 of 22

Olson La Mirada - South Coast Air Basin, Summer

Fire Pumps and Emergency Generators

Equipment Type	Number	Hours/Day	Hours/Year	Horse Power	Load Factor	Fuel Type
Boilers						
Equipment Type	Number	Heat Input/Day	Heat Input/Year	Boiler Rating	Fuel Type	
User Defined Equipment						
Equipment Type	Number					
14.0 Verstetion						